


Submittal Sheets

Universal Clamps

Nom. Size for E.M.T. Rigid Copper Clamps	O.D. Range Min./Max.	Wt./ 100 Pcs.	Std. Pkg.
3/8"	0.557 to 0.675	12	100
1/2"	0.706 to 0.840	13	100
3/4"	0.922 to 1.050	14	100
1"	1.163 to 1.315	18	100
11/4"	1.510 to 1.660	21	50
11/2"	1.740 to 1.900	23	50
2"	2.197 to 2.375	25	50



ORDERING: Specify figure number and pipe size.



SPECIFICATIONS

GENERAL

H-STRUT Pipe Clamps are all manufactured to fit into the standard openings of 1%" channel to support runs of piping where desired, to secure the pipe in place.

MATERIAL

H-STRUT pipe clamps are manufactured from the following materials:

- ☐ Hot Rolled Steel Sheet ASTM A-1011or Cold Rolled Steel Sheet ASTM A-1008
- ☐ Stainless Steel-Type 304/316L...ASTM A-240
- ☐ Aluminum Clamps 5052H32....ASTM B-209

FINISH

H-STRUT pipe clamps are available in the following finishes:

- ☐ Electro Galvanized ASTM B-633
- ☐ Hot Dipped Galvanized......ASTM A-123
- □ Zinc Trivalent Chromium. ASTM B-633-85
- □ Powder Coated Supr-Green ASTM B-117
- ☐ Copper Plated.....ASTM B-734-84

ORDERING

Please specify catalog number, size and finish.

Project Information					
Project:			Notes:		
Address:					
Contractor:					
Engineer:		Date:			
Approval Approval					
☐ Approved	Signature:		Remarks:		
☐ Approved as Noted					
☐ Not Approved					