Tape & Adhesive

Roll

/Case

100

Price

/Each

Scotch

er 334

Priced per Roll

**Qty Price** 

Qty /Each

Priced per Roll

**Qty Price** 

Qty /Each

#### **Electrical Tape**

- Vinyl plastic
- Excellent recovery, molds snugly to any surface Ideal for electrical splicing and insulation;
- protection against solvents and corrosion For use between -7°C and 80°C
- Thickness: 7 mils

#### CSA approved Priced per Roll Model **Qty Price** Price No. Colour Dimensions /Fach Qty /Each PA665 Black 3/4" x 60' (18 mm x 18 m) XC545 Red 3/4" x 66' (18 mm x 20.1 m) XC546 Green 3/4" x 66' (18 mm x 20.1 m) XC547 Blue 3/4" x 66' (18 mm x 20.1 m) XC548 White 3/4" x 66' (18 mm x 20.1 m) XC549 Yellow 3/4" x 66' (18 mm x 20.1 m)

#### **Temflex™ Electrical Tape**

- General purpose, flexible vinyl tape designed for indoor or short term use and bundling
- Temperature rating: 176°F/80°C Colour: Black
- Thickness: 7 mil

PC694

• UL and	CSA approved			Priced per Roll
Model No.	Dimensions	Roll /Case	Price /Each	Qty Price Qty /Each
PC695	3/4" x 60' (19 mm x 18.3 m)	100		

## Scotch<sup>®</sup> Super 88 Vinvl Tape

Model No.	Dimensions	Roll /Case	Price /Each	Qty Price Qty /Each
<ul> <li>Aggressi conforma moisture</li> <li>Will performant</li> <li>Conform</li> <li>Thickness</li> <li>Colour: B</li> <li>UL and C</li> </ul>	nedium voltage cable splic ve adhesive and elastic baa ation to irregular surfaces f tight electrical and mecha orm in a continuous tempe nent up to 220°F (105°C) able for cold weather appl s: 8.5 mils lack SA approved	cking ensures easy for anical protection erature ications: 0°F (-18°C		Priced per Roll
insulatio	ner, premium grade vinyl ta n up to 600 V or protective	jacketing		Scotta

100

#### Scotch<sup>®</sup> 130C Linerless **Rubber Splicing Tape**

3/4" x 66' (19 mm x 20.1 m)

- Highly conformable, linerless self-bonding ethylene propylene rubber (EPR) tape for insulating all solid dielectric cables up to 69 kV
- Excellent thermal dissipation of splice heat Meets industry specifications, excellent physical and electrical properties
- Immediate moisture sealing and void-free buildups Rated up to 194°F (90°C) continuous operation
- and up to 266°F (130°C) short-term overload service Having no liner makes jobs easier and saves time
- Thickness: 30 mils

per Roll

				Priced per Koll
Model No.	Dimensions	Rolls/Case	Price/Each	Qty Qty Price/Each
XC323	1" x 30'	24		

#### **Colourflex™** Tape

General purpose colour coding vinyl tape

Thickness: 7 mils					Priced per Roll
Model No.	Colour	Dimensions	Roll /Case	Price /Each	Qty Price Qty /Each
XC316	Blue	3/4" x 60'	100		
XC317	Green	3/4" x 60'	100		
XC318	Red	3/4" x 60'	100		
XC319	White	3/4" x 60'	100		
XC320	Yellow	3/4" x 60'	100		
XC321	Orange	3/4" x 60'	100		
	-				



Scotch<sup>®</sup> Super 33+ Vinyl Tape All weather, premium grade vinyl tape for primary

insulation up to 600 V or protective jacketing for

Aggressive adhesive and elastic backing ensures easy

conformation to irregular surfaces for moisture tight

Conformable for cold weather applications: 0°F (-18°C)

low/medium voltage cable splices and repairs

electrical and mechanical protection

environment up to 220°F (105°C)

Thickness: 7 mil

• UL and CSA approved

Colour: Black

Model

PC693

No.

.

Will perform in a continuous temperature

Dimensions

3/4" x 66' (19 mm x 20.1 m)

Premium grade vinyl electrical colour-coding tape for

Scotch<sup>®</sup> 35 Colour

**Coding Vinyl Tape** 

phase and job identification and safety

Heavy-duty, premium grade Temperature rating: 220°F/105°C

Thickness: 7 mil

Blue	1/2" x 20"	100		
Green	1/2" x 20'	100		
Red	1/2" x 20'	100		
White	1/2" x 20'	100		
Yellow	1/2" x 20'	100		
Orange	1/2" x 20'	100		
Blue	3/4" x 66'	100		
Green	3/4" x 66'	100		
Red	3/4" x 66'	100		
White	3/4" x 66'	100		
Yellow	3/4" x 66'	100		
Orange	3/4" x 66'	100		
	Green Red White Yellow Orange Blue Green Red White Yellow	Green         1/2" x 20'           Red         1/2" x 20'           White         1/2" x 20'           Yellow         1/2" x 20'           Orange         1/2" x 20'           Blue         3/4" x 66'           Green         3/4" x 66'           Red         3/4" x 66'           White         3/4" x 66'           Yellow         3/4" x 66'	Green         1/2" x 20'         100           Red         1/2" x 20'         100           White         1/2" x 20'         100           Yellow         1/2" x 20'         100           Orange         1/2" x 20'         100           Blue         3/4" x 66'         100           Green         3/4" x 66'         100           Red         3/4" x 66'         100           White         3/4" x 66'         100           Yellow         3/4" x 66'         100	Green         1/2" x 20'         100           Red         1/2" x 20'         100           White         1/2" x 20'         100           Yellow         1/2" x 20'         100           Orange         1/2" x 20'         100           Blue         3/4" x 66'         100           Green         3/4" x 66'         100           Red         3/4" x 66'         100           White         3/4" x 66'         100           Yellow         3/4" x 66'         100           Yellow         3/4" x 66'         100

#### Scotch® 27 Glass **Cloth Electrical Tape**

- Ideal for electrical maintenance applications Woven glass cloth tape with a rubber thermosetting pressure-sensitive adhesive
- Edge-tear resistant,
- conformable, abrasion resistant For use as a coil cover, anchor,
- banding and core, layer and crossover insulation, and for heat-stable insulation for furnace and oven controls, motor leads, and switches Thickness: 7 mils
- UL recognized 130°C/266°F

Model No. Dimensions XC322 3/4" x 66' (19 mm x 20.1 m)



# **Priced per Roll** Qty Qty Price/Each



Rolls/Case

50

Price/Each

2016 © TENAQUIP Limited

www.tenaquip.com

### 1-800-661-2400