


Catalog No. 1SVR405501R2010

Description: CR-S012VDC1R Pluggable interface relay 1c/o, A1-A2=12VDC, Output=6A/250VAC

UPC No 4013614499104

Home > Controls & Protective Relays > Interface Relays & Optocouplers



Descriptors

Category	Interface Relays & Optocouplers
----------	---------------------------------

Specifications

Function	Pluggable slim interface relay CR-S
Rated Control Supply Voltage	12 V DC
Output Signal	250 V / 6 A
Output	1 c/o (SPDT) contact
Contact material	silver-tin-oxide (AgSnO2)
Product Main Type	CR-S
Sub-Function	Relay with standard contacts
Ambient Air Temperature	Operation -40 ... +85 °C Storage 0 ... +40 °C
RoHS Status	Following EU Directive 2011/65/EU
Object Classification Code	K

Classifications

ETIM 4	EC001437 - Switching relay
ETIM 5.0	EC001437 - Switching relay
ETIM 6.0	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	7.0 27371601

Dimensions

Product Net Width	5 mm
Product Net Height	15 mm
Product Net Depth / Length	28 mm
Product Net Weight	0.005kg

Package Information

Package Information

Package Level 1 Units	10 piece
Package Level 1 Width	300 mm
Package Level 1 Height	23.7 mm
Package Level 1 Depth / Length	7.4 mm
Package Level 1 Gross Weight	0.06 kg
Package Level 1 EAN	4013614486432

Ordering

Minimum Order Quantity	10
Customs Tariff Number	85364900
ECCN	N
ECN	N
ABB MDF Code	3DL - Relays (LV / Control + Protection)
ABB Business Unit	ELSP - Smart Power