


PS1-2-2-65



PS1-2-2-65 Busbar



General Information

| | |
|-----------------------|---|
| Extended Product Type | PS1-2-2-65 |
| Product ID | 1SAM201906R1122 |
| EAN | 4013614400766 |
| Catalog Description | PS1-2-2-65 Busbar |
| Long Description | PS1-2-2-65 3-phase busbar for 2 MS116 / MS132 with 2 HK/SK, I _e =65A |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85369010 |

Popular Downloads

| | |
|-----------------------------------|---|
| Data Sheet, Technical Information | 1SBC100192C02-- |
| Instructions and Manuals | 2CDC131011M6802 2CDC131034M6801 2CDC131022M6802 |
| Dimension Diagram | 1SAM200450F0009 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 104.5 mm |
| Product Net Height | 32.3 mm |
| Product Net Depth / Length | 13 mm |
| Product Net Weight | 0.04 kg |

Technical

| | |
|---|----------------------|
| Rated Operational Voltage | 690 V AC 250 V DC |
| Rated Operational Current (I _e) | 65 A |
| Rated Impulse Withstand Voltage (U _{imp}) | 6 kV |
| Rated Short-time Withstand Current (I _{cw}) | 100 kA |
| Number of Mountable Devices | 2 |
| Number of Lateral Auxiliary Contacts | 2 |
| Number of Phases | 3 |

| | |
|----------------------------|--|
| Degree of Protection | IP20 |
| Pollution Degree | 3 |
| Connection Type | Fork |
| Standards | IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1 |
| Product Name | Busbar |
| Suitable For | MS116 MS132 |
| Suitable for Product Class | Manual Motor Starter |
| Accessory Group | Electrical |
| Accessory Type | 3-Phase Busbar |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -50 ... +80 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

Technical UL/CSA

| | |
|----------------------------------|-----------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC |
| Ampere Rating UL/CSA | 65 A |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|---|
| cUL Certificate | 1SAA963001-1701 |
| Declaration of Conformity - CE | 1SAD938511-0056 |
| GOST Certificate | 1SAA937000-2703 |
| Instructions and Manuals | 2CDC131011M6802 2CDC131034M6801 2CDC131022M6802 |
| RoHS Information | 1SAD938511-0056 |
| UL Certificate | 1SAA963001-1602 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 80 mm |
| Package Level 1 Depth / Length | 120 mm |
| Package Level 1 Height | 46 mm |
| Package Level 1 Gross Weight | 0.43 kg |
| Package Level 1 EAN | 4013614488146 |
| Package Level 1 Units | 10 piece |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | W |
| ETIM 4 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5 | EC000215 - Phase busbar |
| ETIM 6 | EC000215 - Phase busbar |

