

Alternate Catalog No. VM4
Catalog No. 1SBN030105T1000

Description: VM4 Mechanical Interlock Unit

UPC No 3471523130609

Home > Contactors & Starters > UL Listed IEC Contactors > AF Contactors

Mechanical interlock units The VM mechanical interlock units are designed for the interlocking of two AF contactors. When mounted between two contactors, the VM mechanical interlock unit prevents one of the contactors from closing as long as the other contactor is closed. The mechanical interlock units VM4 and VM96-4 include 2 fixing clips (BB4).

Representative Image

Descriptors

Category	AF Contactors
Block Contactor Type	Accessory

Specifications

Product Type	AF
RoHS Status	Following EU Directive 2011/65/EU
Maximum Mechanical Switching Frequency	1800 cycles per hour

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 6.0	EC001044 - Mechanic interlock for switch
ETIM 7	EC001044 - Mechanic interlock for switch
ETIM 5.0	EC002498 - Accessories for low-voltage switch technology

Dimensions

Product Net Weight	0.005kg
--------------------	---------

Package Information

Package Level 1 Width	120 mm
Package Level 1 Depth / Length	180 mm
Package Level 1 Units	bag 10 piece
Package Level 3 Units	2400 piece
Package Level 2 Gross Weight	0.5 kg

Ordering

Minimum Order Quantity	10
------------------------	----

