American Standard

## COLONY® PRO TWO-HANDLE KITCHEN FAUCET WITH HIGH-ARC BRASS SWIVEL SPOUT



#### **GENERAL DESCRIPTION:**

Durable metal construction. 1/4 turn washerless ceramic disc valve cartridges witht one-half inch male inlet shanks. High-arc brass swivel spout and metal lever handles. Color-matched side spray. 1.5 gpm/5.7 L/min. maximum flow rate.

#### **PRODUCT FEATURES:**

**Ceramic Disc Valve Cartridge:** Assures a lifetime of drip-free performance.

**Lead Free:** Faucet contains  $\leq 0.25\%$  total lead content by weighted average.

**Simple Installation:** Fast and easy one person installation. Faucet drops in from top. Quick spin nuts secure faucet in place.

#### SUGGESTED SPECIFICATION

Two handle kitchen faucet shall feature metal construction with one-half inch male inlet shanks and high-arc brass swivel spout. Shall also feature 1/4 turn washerless ceramic disc valve cartridges. Faucet shall be American Standard Model #7074.55\_\_.\_\_\_.

American Standard

### **CODES AND STANDARDS**

These products meet or exceed the following codes and standards:

ANSI A117.1 ASME A112.18.1 CSA B125.1 NSF 61/Section 9 NSF 372

# COLONY<sup>®</sup> PRO TWO-HANDLE KITCHEN FAUCET WITH HIGH-ARC BRASS SWIVEL SPOUT



1.5 gpm/5.7 L/min. FLOW RATE

|          |   | Finish<br>Options  |
|----------|---|--------------------|
| Product  |   | Polished<br>Chrome |
| Number   | Description   | 002                |
| 7074.550 | Kitchen faucet. Lever handles. LESS handspray.                    |                    |
| 7074.551 | Kitchen faucet. Lever handles. Separate color-matched side-spray. |                    |

Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.