NINJA® MAX

99-1-9754

AVAILABLE SIZES S-XL (7-10)



FEATURES

- + Cut resistant Dyneema® shell
- + Bi-polymer coating
- + Elastic wrist
- + Treated with Actifresh® to eliminate bacteria



APPLICATIONS

Injection molding operations

Sheet metal operations

Automotive manufacturing

STANDARDS



4542

ANSI Cut Level 3 EN 388 4542

> * All ratings are tested and verified by third party companies.



Bob Dale Gloves Canada 4504 - 82 Ave. Edmonton, AB T6B 2S4 Ph/Tel: (780) 469-2100 | 1-800-661-7303 BOBDALEGLOVES.COM

Bob Dale Gloves USA 1171 N. Fiesta Blvd. Gilbert, AZ 85233 Toll Free: 1-855-215-7113

LABELING

Country of origin sewn in cuff, Dyneema® tag sewn outside cuff Ninja Max logo, CE cut rating, & style no stamped on back hand

PACKAGING

12 PR per polybag 120 PR per carton

Revision date: 02/08/2019

document is subject to Imports Ltd. cannot contritions under which this product may be us the information in Specific contact of the provident un extent permitted by Jaw, Bob Dale Gloves and Imp its affiliates, employees or representatives will not be re mages of any nature resulting from the use or reliar iomation contained in this data sheet. No express o