

BARIL

PRO

Fiche Technique / Spec Sheet

RVA-9181-00-P

RVA-9181-P0-P
RVA-9181-W0-P

Description

- Brut de valve pression équilibrée à contrôle de volume avec dérivateur 2 voies
- Robinet de type P à contrôle du débit et de la température
- Soupapes anti-retour et d'arrêt intégrées
- Dérivateur 2 voies à positions partagées
- *Rough-in pressure balanced volume control valve with 2-way diverter*
- *Type P faucet with flow and temperature control*
- *Built-in check-stop valves*
- *2-way diverter, non-shared ports*

Cartouches / Cartridges

- CAR-1001-35-P
- CAR-1020-40-P

Certifications / Standards


- ASME A112.18.1 / CSA B125.1
- ASSE 1016

Débit / Flow rate


19 L/min @ 60 psi
5 gpm @ 60 psi



- **RVA-9181-00-P:** Raccordements 1/2" NPT ou cuivre soudé
- **RVA-9181-P0-P:** Raccordements 1/2" PEX aux entrées et aux sorties
- **RVA-9181-W0-P:** Raccordements 1/2" PEX EXPANSION aux entrées et aux sorties
- **RVA-9181-00-P:** 1/2" NPT or welded copper connections
- **RVA-9181-P0-P:** 1/2" PEX for inlets and outlets connections
- **RVA-9181-W0-P:** 1/2" PEX EXPANSION for inlets and outlet connections



RVA-9181-P0-P



RVA-9181-W0-P

