



□ **060304A** 

610mm (24") stainless steel slide bar,  
1778 mm (70") white vinyl hose, push button  
handshower head with back flow protection,  
wall supply elbow & flange.

- Shower MAX flow 2.5 gpm @ 80 psi  
(9.5 L/min @ 552 kPa)
- Shower MIN flow 2.0 gpm @ 45 psi  
(7.6 L/min @ 310 kPa)
- See Notes 1 & 2



**Specification: (example)**

Handshower head with push button pause.  
Back flow protection provided by two integral certified  
check valves in series, which operate independently  
and are non-serviceable, ASME A112.18.3 and  
ASME A112.18.1 / CSA B125.1.

□ **061226A**

- Shower MAX flow 2.5 gpm @ 80 psi  
(9.5 L/min @ 552 kPa)
- Shower MIN flow 2.42 gpm @ 45 psi  
(9.16 L/min @ 310 kPa)
- See Notes 1 & 2



□ **RP7405**

- Shower MAX flow 2.0 gpm @ 80 psi  
(7.6 L/min @ 552 kPa)
- Shower MIN flow 1.7 gpm @ 45 psi  
(6.44 L/min @ 310 kPa)
- See Notes 1 & 2



□ **59462-WHB15-BG** 

- Shower MAX flow 1.5 gpm @ 80 psi  
(5.7 L/min @ 552 kPa)
- Shower MIN flow 1.13 gpm @ 45 psi  
(4.3 L/min @ 310 kPa)
- See Notes 1 & 2



**Note 1**

Showerheads/handshowers are for use with automatic compensating valves rated at or less than the Shower MIN flow rate value.

**Note 2**

**PAUSE WARNING – FOR HANDSHOWER**

Plumbing Codes require that showerheads and handshowers provide a small but continuous flow of water (trickle) when in "PAUSE" mode. Because of this continuous flow, in certain circumstances pressure variations in the water line and/or changes in the position of the shower temperature control handle while in "PAUSE" mode could result in dramatic changes to the temperature of the water when the shower head or hand shower is returned to the "ON" position.

ALWAYS point the shower head away from yourself when returning to the "ON" position and feel the water with your hand before resuming your shower to ensure the water flow is not too hot or too cold.

DO NOT allow children or others who might not understand this warning to use the "PAUSE" function.

**Specification: (example)**

Brass body diverter valve, ADA compliant lever handle, polished chrome-plated metal trim.

 **061058A**

 **060274A**

76 mm (3") Diameter wall thermometer, 18 to 82° C (0 to 180° F), stainless steel construction with shatterproof Lexan lens, complete with cast brass tee, polished chrome-plated brass nipple and set screw wall flange.


 **54T1200**

With 70mm (2-3/4") ADA compliant lever blade handle and integral stop. In-wall, volume control stop, TUF-TECK® institutional structure, polished chrome-plated finish exposed metal trim, color indexed metal handle with vandal resistant screw, 1/2" FIP inlet/outlet.


 **U4760-PK**

Brass body volume control, polished chrome plated finish, flow adjustment lever handle, 1/2" NPS inlet/outlet.


 **060605A**

Forged brass Toe Tester Spout, polished chrome-plated finish, 1/2" FIP inlet.


 **060710A**

Bent Shower arm, metal set screw wall flange.


 **RP7406**

Swivel handshower connector with hole for vertical mounting pin, 1/2" NPS inlet & outlet, plastic and chrome-plated.


 **060303A**

Brass wallmounted elbow, flange, polished chrome-plated finish, 1/2" NPT inlet & outlet.


 **060798A**

1/2" NPT inlet/outlet polished chrome-plated brass atmospheric in-line vacuum breaker. Certified under ASSE 1011/CSA B64.2.


 **U494R-WH70-PK**

1778 mm (70") long white vinyl handshower hose, nylon reinforced.


 **U495D-69-PK**

1753 mm (69") long chrome-plated stainless steel handshower hose stretches to 2337 mm (92").


 **U7500**

Quick disconnect connectors for handshower hose.

