





▲ Designate Proper Finish Suffix

# BRIZO

## BATHROOM FAUCET

- Kintsu<sup>®</sup> Collection
- Two Handle Widespread Deck Mount

#### **STANDARD SPECIFICATIONS:**

- Max flow rate 1.5 gpm @ 60 psi, 5.7 L/min @ 414 kPa
- Max flow rate (ECO model only) 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- · Three hole mount
- Control mechanism is a rotating cylinder ceramic cartridge with 90° rotation
- 1/2-14 NPSM threaded inlets
- Solid brass fabricated end valve and spout bodies
- · Spout features laminar water flow
- LHP Less Handle Program. See handle options below
- Note: Optional red/blue temperature indicator rings, order RP101684

### WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.); or for commercial purchasers, 1 year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.
- Please go to www.brizo.com for the complete details of our limited warranty.



#### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®
- L ICC/ANSI A117.1