



FOAM-A-COIL™

Condenser and Evaporator Coil Cleaner

[Description](#) | [Characteristics](#) | [Applications](#) | [Packaging](#) | [Instructions](#) | [Precautions](#) |
[Specifications](#) |
[Limited Warranty](#)

DESCRIPTION:

Foam-A-Coil™ is a non-acid high foaming cleaner for condenser coils, evaporator coils, mechanical equipment and air filters. Foam-A-Coil™ penetrating, surfactant aided, foaming action lifts and removes grime, oil, grease and dust from air conditioning, refrigeration coils, air handling and mechanical equipment. Foam-A-Coil™ requires no special ventilation and is biodegradable.

[Top of Page](#)

CHARACTERISTICS:

-
- Foaming action penetrates stubborn grease, tars and dirt. It disperses them so they can be rinsed away with water.
 - Biodegradable
 - Non-Acid, can be use indoors and outdoors
 - Will not harm copper or aluminum
 - Concentrated - dilute with water for economical use.

[Top of Page](#)

APPLICATIONS:

Foam-A-Coil™ can be safely used on aluminum, copper, stainless steel or washable painted surfaces. It is formulated to clean metal coils, fibers and metal mesh filters, and other metal surfaces where acids cannot be used.

For industrial use only by trained professional personnel.

[Top of Page](#)

PACKAGING:

Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
82632	Gallon (3.8 L)	4 bottles	36	1.21
82634	5 Gallons (18.9 L)	1 pail	45	1.10
82638	55 Gallons (208 L)	1 drum	535	9.01
82640	12 oz. Aerosol	12 cans	13	0.51

[Top of Page](#)

INSTRUCTIONS:

**READ ALL DIRECTION AND WARNINGS ON LABEL BEFORE USING
*CONCENTRATE***

1. Appropriate dilution with water is the key to effective and economic use.

For extremely dirty coils and equipment: dilute with 4 to 5 parts of water.

For a Continuous Maintenance Program: dilute with 6 to 10 parts of water.

2. Shake or mix before use.

3. Apply the diluted solution with the Stewart Hall™ Penetrator Sprayer™ or other sprayer for small to medium jobs. Use a brush to help faster penetration for especially hard or encrusted dirt.

4. Allow 5 to 10 minutes of soaking time.

5. On evaporator coil, rinsing is not required, provided system is operating.

AEROSOL

1. Shake well before using.

2. Spray area thoroughly and allow to soak for several minutes.

3. Wipe clean or flush with water.

SPECIAL NOTE: On waxed and painted coils, Foam-A-Coil™ should be rinsed off within a minute of application to avoid the possibility of removing wax or fading the paint.

For additional technical information, call Toll Free 1-800-231-3345.

[Top of Page](#)

PRECAUTIONS:

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,

CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

CONTAINS: Organic cleaners and inorganic disperants. PRECAUTIONS: Avoid contact with skin and eyes. Use protective eye wear and protective gloves. Do not take internally. **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **Eyes and Skin** - Flush with large amounts of clean water for at least 15 minutes. **Inhalation** - Remove to fresh air. Give oxygen or artificial if needed. **Ingestion** - INDUCE VOMITING. Only if conscious, give large amounts of water, then milk of magnesia. If unconscious, do not give anything by mouth or attempt to induce vomiting. Call a physician immediately. **FIRE AND SPILLS:** For fire, use water fog, CO2, foam or dry chemicals to extinguish. For spills, shut off ignition sources, ventilate confined areas and wipe up with absorbent materials to prevent footing hazard. **STORAGE AND HANDLING:** Store in cool place away from all food. Keep container upright and tightly closed when not in use. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

[Top of Page](#)

SPECIFICATIONS:

Wt/Gal @ 77 degree F	8.5+-0.5 lbs/gal.
Flash Point SETA CC	None
Color	Bright yellow/ Green
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

[Top of Page](#)

LIMITED WARRANTY:

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

[Top of Page](#)

MANUFACTURED IN U.S.A. BY

RectorSeal®

2601 Spenwick Drive • Houston, TX 77055 USA

713-263-8001 • Fax 713-263-7577

Toll-free 800-231-3345 • Fax 800-441-0051

[Back](#)