



ZIPP™ II

Environmentally Safer Quick Drying Degreaser

[Description](#) | [Characteristics](#) | [Applications](#) | [Packaging](#) | [Instructions](#) | [Precautions](#) | [Specifications](#) | [Limited Warranty](#)

DESCRIPTION:

Zipp™ II is an environmentally safer quick drying degreaser that removes grease, oil, wax, tar, gum, grime, dirt, carbon, and greasy stains from most hard surfaces. It will not short out electrical equipment. It may be used on oil burner parts, compressors, refrigeration units, greasy fan blades, strainers, engines, stoves, relay contact points, and electrical equipment.

[Top of Page](#)

CHARACTERISTICS:

- Non-chlorinated
- Non-flammable
- Non-conductive
- Contains no carbon tet
- Contains no restricted solvents
- Excellent degreaser cleaner
- Leaves no residue
- Fast drying

[Top of Page](#)

APPLICATIONS:

Zipp™ II may be used on most dirty, greasy surfaces. It is great for use on electric motors, fan blades, compressors, all oil burner parts, strainers, engines, stoves, contact points, and refrigeration units.

[Top of Page](#)

PACKAGING:

Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
82645	12 oz. aerosol	12	13	0.52

[Top of Page](#)**INSTRUCTIONS:**

-
1. Shake can well before using.
 2. Thoroughly saturate part to be cleaned.
 3. For heavy grease and grime deposits allow five minutes soaking time. Some agitation with a brush or rag is very helpful.
 4. Allow to air dry.

DO NOT USE ON PLASTICS WITHOUT TESTING FIRST.

For additional technical information, call Toll Free 1-800-231-3345.

[Top of Page](#)**PRECAUTIONS:**

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

W A R N I N G !

CONTENTS UNDER PRESSURE. VAPOR HARMFUL - AVOID BREATHING VAPOR.

READ BACK PANEL CAREFULLY

WARNING - Use only as directed with adequate ventilation. **Keep out of reach of children.** Do not spray into fire or on hot surfaces. Do not puncture or incinerate can. Avoid contact with food. Do not expose to heat or store at temperature above 120 degree F.

FIRST AID: Skin: Wash off with soap and water. **Eyes:** Flush with water for 15 minutes. Seek medical attention if irritation persists. **Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped, and oxygen if available. Call physician immediately.

For additional information, refer to Material Safety Data Sheet.

[Top of Page](#)

SPECIFICATIONS:

Wt/Gal	11.90 lbs
Flash Point	N/A
Flame Extension	None
Odor	Sweet
Color	Clear
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

[Top of Page](#)

LIMITED WARRANTY:

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

[Top of Page](#)

MANUFACTURED IN U.S.A. BY

RectorSeal®
2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • fax 713-263-7577
Toll-free 800-231-3345 • fax 800-441-0051

[Back](#)