


Wiring Devices | Plugs & Connectors

Standard Grade
Thermoplastic
Plugs & Connectors2-Pole, 2-Wire Non-Grounding
15A, 125V/AC

FEATURES

- Tough thermoplastic construction.
- Plug blades firmly embedded in body.



1912




3123

Thermoplastic Plugs & Connectors

15A 125V/AC

Description	Cord Diameter	Color or Color Suffix	Plug	Catalog No.	Connector
NEMA 1-15, Flat Handle Body	0.31" (7.9mm)	B, W	□ 1912	•	—
NEMA 1-15, Round Body	0.41" (10.4mm)	BK	□ 3123	•	—
NEMA 1-15, Cylindrical Body	0.25-0.67" (6.4-17.0mm)	Orange	—	□ 6882	•

UL SP NOM 426 Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 6882

Standard Grade
Thermoplastic
Plugs & Connectors2-Pole, 3-Wire Grounding
15A, 125V/AC

FEATURES

- Tough thermoplastic construction.
- Plug blades firmly embedded in body.



6867



6887

Thermoplastic Plugs & Connectors

15A 125V/AC

Description	Cord Diameter	Color	Plug	Catalog No.	Connector
NEMA 5-15, Cylindrical Body	0.67" (17.0mm)	Orange	□ 6867	•	□ 6887

UL SP NOM 426 Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified

Color Ordering Information: For ordering devices, include Cat. No. followed by the color code if applicable: B (Brown), BK (Black), W (White)

Dimensional Information: B-63

Specification Information: Please visit www.cooperwiringdevices.com

NAFTA Compliant: See page F-21