# Specifications

## Eaton 7310B

Eaton safety grip locking receptacle, #14-8 AWG, 20A, Industrial, 125/250V, Back and side wiring, Black, Single, Non-NEMA, Three-pole, Three-wire, Glass-filled nylon

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Arrow Hart locking receptacle |
| **CATALOG NUMBER** | 7310B |
| **UPC** | 040893681450 |
| **PRODUCT LENGTH/DEPTH** | 1.62 in |
| **PRODUCT HEIGHT** | 3.28 in |
| **PRODUCT WIDTH** | 1.03 in |
| **PRODUCT WEIGHT** | 0.25 lb |
| **COMPLIANCES** | Federal Specifications Classification W-C375 |
| **CERTIFICATIONS** | UL Listed<br>cULus Listed |
| **PRODUCT TYPE** | Locking receptacle |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **SPECIAL FEATURES** | Watertight locking receptacle |
| **TYPE** | Locking receptacle |
| **AMPERAGE RATING** | 20A |
| **VOLTAGE RATING** | 125/250 V |
| **CONTACT MATERIAL** | Brass |
| **APPLICATION** | Industrial |
| **DEVICE GRADE** | Heavy-duty specification grade |
| **WIRING METHOD** | Back and side |
| **NUMBER OF WIRES** | 3<br>Non-grounding |
| **NUMBER OF POLES** | Three-pole |
| **COLOR** | Black |
| **MATERIAL** | Glass filled nylon |
| **OPERATING TEMPERATURE** | -40 to 60 °C (-40 to 140 °F) |
| **ALLOWABLE WIRE SIZE** | #14-8 AWG Copper, or Copper-Clad Aluminum |
| **NEMA CONFIGURATION** | Non-NEMA |
| **TORQUE RATING** | 20 lbf-inch |
| **DESIGN TYPE** | Single receptacle |
| **FACE/BODY MATERIAL** | Glass filled nylon |
| **RECEPTACLE TYPE** | Single |

## Resources

| | |
|---|---|
| MULTIMEDIA | Arrow Hart - Connecting Safety to Reliability since 1890 |
| SPECIFICATIONS AND DATASHEETS | Industrial grade 20A Non-NEMA locking devices spec sheet<br><br>Eaton Specification Sheet - 7310B |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.