

Specifications



Photo is representative

Eaton C25BNB230C

Eaton definite purpose contactor, Quick, 30A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, Compact, two-pole, 30A, Contactor, Two-pole, 40A, Binding head screw and quick connect terminals (side-by-side), Non-reversing

General specifications

PRODUCT NAME	Eaton definite purpose contactor
CATALOG NUMBER	C25BNB230C
UPC	786685116044
PRODUCT LENGTH/DEPTH	2.32 in
PRODUCT HEIGHT	3.19 in
PRODUCT WIDTH	1.97 in
PRODUCT WEIGHT	0.7 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized

Product specifications

AMPERAGE RATING	30A
NUMBER OF POLES	Two-pole
TYPE	Non-reversing
COIL	440-480 Vac, 50/60 Hz
ENCLOSURE	Open with metal mounting plate
FRAME SIZE	Compact, two-pole
INDUCTIVE FULL LOAD	30 A
MODEL	Contactator
RESISTIVE LOAD	40 A
TERMINALS	Binding head screw and quick connect terminals (side-by-side)
CONNECTION	Quick

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - C25BNB230C

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

