

Specifications



Photo is representative



Eaton C25ENF440B

Eaton definite purpose contactor, Quick, 40A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 40A, Contactor, Four-pole, 50A, Box lugs (posidrive setscrew) and quick connect terminals, Non-reversing

General specifications

PRODUCT NAME	Eaton definite purpose contactor
CATALOG NUMBER	C25ENF440B
UPC	782113536606
PRODUCT LENGTH/DEPTH	3.38 in
PRODUCT HEIGHT	3.75 in
PRODUCT WIDTH	2.68 in
PRODUCT WEIGHT	2.3 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Recognized CSA Certified
CATALOG NOTES	Resistive Load rating per pole
PRODUCT TYPE	Definite purpose contactor

Product specifications

AMPERAGE RATING	40A
NUMBER OF POLES	Four-pole
TYPE	Non-reversing
COIL	208-240 Vac, 50/60 Hz
ENCLOSURE	Open with metal mounting plate
FRAME SIZE	15-50 A, two-pole and three-pole
INDUCTIVE FULL LOAD	40 A
MODEL	Contactator
RESISTIVE LOAD	50 A
TERMINALS	Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)
CONNECTION	Quick

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - C25ENF440B

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

