

Eaton XTCEXFAC20

Catalog Number: XTCEXFAC20

Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, 2NO contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC20
UPC	EAN
786689004958	4015082764227
Product Length/Depth	Product Height
1.5 in	1.5 in
Product Width	Product Weight
2.5 in	0.1 lb
Compliances	Certifications
CE Marked	IEC 60947
ATEX Compliant	EN 60947
CCC Marked	UL Listed
	CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

defaultTaxonomyAttributeLabel

Number Of Poles

Two-pole

Type

Contactor Accessory - Auxiliary Contact

Used with

XTRE control relays

Terminals

Screw

Contact configuration

2 NO

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Conventional thermal current

16A

Quantity

5

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC20](#)

[Global Data Sheet - XTCEXFAC20](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia