

Eaton XTCEXFAC31

Catalog Number: XTCEXFAC31

Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 3NO-1NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC31
UPC	EAN
786689004972	4015082764272
Product Length/Depth	Product Height
1.5 in	1.5 in
Product Width	Product Weight
2.5 in	0.1 lb
Compliances	Certifications
CE Marked	IEC 60947
CCC Marked	EN 60947
ATEX Compliant	UL Listed
	CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

defaultTaxonomyAttributeLabel	Resources
Number Of Poles	Catalogs
Four-pole	Eaton's Volume 5—Motor Control and Protection
Type	Specifications and datasheets
Contactor Accessory - Auxiliary Contact	Global Data Sheet - XTCEXFAC31
Used with	Eaton Specification Sheet - XTCEXFAC31
XTRE control relays	
Terminals	
Screw	
Contact configuration	
3 NO-1 NC	
Mounting method	
Front	
Rated operational current	
6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V	
Conventional thermal current	
16A	
Quantity	
5	