Specifications



Photo is representative

Eaton XTRE10B22E

XT IEC Control Relay, Screw terminals, 45 mm - standard Frame size, 2NO-2NC contact configuration, 208V 50 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 4A at 380/400/415V rated operational voltage

General specifications	
PRODUCT NAME	Eaton XT IEC control relay
CATALOG NUMBER	XTRE10B22E
EAN	4015082763930
PRODUCT LENGTH/DEPTH	3 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	0.5 lb
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Control relay

Powering Business Worldwide

Product specifications

CONVENTIONAL THERMAL CURRENT	10A
TYPE	Control relay
FRAME SIZE	45 mm - standard
COIL	208 Vac, 50 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
TERMINALS	Screw terminals
RATED OPERATIONAL CURRENT	4 A at 380/400/415 V 6 A at 220/230/240 V

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTRE10B22E

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.