


# B25RIC-AT

## 5" Shallow IC Remodel Housing

LAMP WATTAGE: (1) MAXIMUM 50W R/PAR30, 40W A19



DESIGNED FOR 2" X 6" JOIST CONSTRUCTION



ITEM SELECTOR: (Please check the boxes below for the option desired)

TYPE	AIR-SHUT	OPTION	TRIM TYPE	BAFFLE	REFLECTOR	TRIM/RING
B25RIC	<input type="checkbox"/> AT	<input type="checkbox"/> (W) With quick connects	<input type="checkbox"/> B531 <input type="checkbox"/> B508 <input type="checkbox"/> B563 <input type="checkbox"/> B502 <input type="checkbox"/> B514	<input type="checkbox"/> W <input type="checkbox"/> P <input type="checkbox"/> SN <input type="checkbox"/> CP <input type="checkbox"/> BZ	<input type="checkbox"/> CL <input type="checkbox"/> RG <input type="checkbox"/> W <input type="checkbox"/> MB <input type="checkbox"/> BZ <input type="checkbox"/> CP <input type="checkbox"/> SN <input type="checkbox"/> SHZ	<input type="checkbox"/> WH <input type="checkbox"/> BK <input type="checkbox"/> SN <input type="checkbox"/> CP <input type="checkbox"/> CH <input type="checkbox"/> PB <input type="checkbox"/> BZ

### Specifications:

B25RIC

AIR-SHUT      OPTION      TRIM TYPE      BAFFLE      REFLECTOR      TRIM/RING

BAFFLE	REFLECTOR	TRIM/RING
W White P Black SN Satin Nickel CP Copper BZ Bronze	CL Chrome RG Gold W White MB Black BZ Bronze CP Copper SN Satin Nickel SHZ Satin Haze	WH White BK Black SN Satin Nickel CP Copper CH Chrome PB Polish Brass BZ Bronze

Sample of Catalog Number: B25RIC-AT-W-B531-W-WH

\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions  
subject to change without notice.

REV: ELITE LIGHTING-SPEC-06-29-2011

Catalog Number:	
Project Name:	Type:
Note:	elite LIGHTING

### DESCRIPTION

Thermally protected, IC rated specification grade remodel recessed housing. For remodeling installations where housing will be in direct contact with insulation. For fast and easy installation in existing plaster or mechanical ceilings from 1/2" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight 1/2" KOs and four Romex knockouts with a strain relief. Accommodates up to 50W PAR30, R30 lamps and 40W A19 lamps.

### SPECIFICATION


**A. HOUSING** - Die-formed, all aluminum construction for maximum heat dissipation and rust protection.

**B. SOCKET** - Medium base screw shell porcelain socket snaps into trim to allow usage of different lamp types, as well as proper and consistent lamp positioning.

**C. INSTALLATION** - Four Preinstalled spring clips which secure the housing firmly into ceiling and accommodate ceiling thickness from 1/2" to 1-3/8".

**D. JUNCTION BOX** - ETL listed for feed through wiring, provided with eight 1/2" KOs and four Romex knockouts with strain relief.

**E. THERMAL PROTECTION** - Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.



BEAM DIA. MEASURED AT 50% OF NAIR F.C.

### FEATURES

- Thermally Protected remodel IC housing.
- Dependable, favorable design and effortless installation.
- Unit slips through 5-1/2" ceiling opening.
- Four Preinstalled spring clips which secure the housing firmly into ceiling to accommodate ceiling thickness from 1/2" to 1-3/8".
- Can be installed from below the ceiling.
- 5 1/2" height allows use in 2" x 6" joist construction.
- Wire through junction box.
- Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

### OPTIONS

#### AIR-SHUT

- Gasket to prevent air flow from heated or air conditioned spaces.
- Meets all national air flow requirements.

# 5" Incandescent Trims

( LAMP WATTAGE: 50W R/ PAR30, 40W A19 )

Catalog Number:

Project Name:

Type:

Note:


**elite** LIGHTING

## B531CP-CP SHALLOW STEPPED BAFFLE



**AVAILABLE COLOR COMBINATIONS:**  
CP-CP, SN-SN, W-WH,  
P-WH, P-BK, BZ-BZ

**TO BE USED  
WITH B25IC-AT  
& B25RIC-AT  
HOUSING ONLY**




## B508RG-WH SHALLOW REFLECTOR




**AVAILABLE COLOR COMBINATIONS:**  
CP-CP, W-WH, RG-WH,  
MB-WH, CL-WH, MB-BK,  
RG-PB, CL-CH


**TO BE USED  
WITH B25IC-AT  
& B25RIC-AT  
HOUSING ONLY**



## B563PB PAR30 GIMBAL TRIM




**TRIM/RING FINISH:**  
WH, BK, SN, CP, CH,  
PB, BZ



## B502SN EYEBALL



**TRIM/RING FINISH:**  
WH, BK, SN, CP, CH,  
PB, BZ




## B514WH SHOWER TRIM



FOR  
**WET**  
LOCATION

**TRIM/RING FINISH:**  
WH

**TO BE USED  
WITH B25IC-AT  
& B25RIC-AT  
HOUSING ONLY**



BAFFLE	REFLECTOR	TRIM RING
<b>W</b> White	<b>CL</b> Chrome	<b>WH</b> White
<b>P</b> Black	<b>RG</b> Gold	<b>BK</b> Black
<b>SN</b> Satin Nickel	<b>W</b> White	<b>SN</b> Satin Nickel
<b>CP</b> Copper	<b>MB</b> Black	<b>CP</b> Copper
<b>BZ</b> Bronze	<b>CP</b> Copper	<b>CH</b> Chrome
	<b>SN</b> Satin Nickel	<b>PB</b> Polish Brass
		<b>BZ</b> Bronze

*\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.*