

# BL4IC

## 4" Miniature Low Voltage IC Housing

LAMP WATTAGE: (1) MAXIMUM 12V 50W MR16


Catalog Number:

Project Name:


Type:

Note:

elite LIGHTING



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION



### DESCRIPTION

Small aperture low voltage, thermally protected IC rated, specification grade recessed shallow housing. Designed for new construction. Accommodates up to 35W MR16 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four 1/2" KOs, one 3/4" KO and four Romex knockouts with strain relief.

### SPECIFICATION

**A. OUTER HOUSING** - Die-formed aluminum construction for maximum heat dissipating air chamber on top of the housing. Junction box could be accessed from inside and outside housing.


**B. INNER HOUSING** - Deep-drawn single piece aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame to accommodate 1/2" to 1-3/8" ceiling.

**C. TRANSFORMER** - Enhanced in heat dissipating cover, to provide noise free operation. Attached to junction box cover so it may be serviced from below the ceiling. Thermally protected.

- **M**-Class H dimming magnetic transformer.
- **E**-Class II dimming electronic transformer (LighTech part #LET 75 BF)
- **TOR**-Class H dimming toroidal transformer, providing 35% more lumens than traditional transformers. Constructed of M3 grade silicone steel. (Must use dimmers rated for electromagnetic transformer)

**D. BAR HANGERS** - Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span and can be shortened for 12" joists. Integral bar hanger nailers are designed to be hammered directly into the joist without additional nails or screws and makes installation fast and accurate. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting methods if necessary.

**E. JUNCTION BOX** - ETL and UL listed for through-branch circuit wiring and has four 1/2" KOs, one 3/4" KO and four Romex knockouts with true pry-out slots and strain clamps.



### FEATURES

- Integral low voltage magnetic transformer to prolong lamp life and increase lighting quality.
- Thermally Protected IC housing.
- Designed for accent and task lighting applications.
- Wire through junction box.
- Preinstalled adjustable bar hangers.
- Dependable, favorable design and effortless installation.
- 7-1/4" height allows use in 2" x 8" joist construction.
- Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.

### OPTIONS

#### 1. AIR-SHUT

- Gasket to prevent air flow from heated or air conditioned spaces.
- Meets all national air flow requirements.

### UL AND C-UL/ETL AND C-ETL LISTED

For Damp location  
For Feed-through wiring  
For Direct contact with insulation



BL4IC - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	TRIM TYPE						BAFFLE	TRIM RING	MR 16 LENS FILTER	
<input type="checkbox"/> 20W	<input type="checkbox"/> B1451 <sup>1</sup>	<input type="checkbox"/> B1476 <sup>2</sup>	<input type="checkbox"/> B1494	<input type="checkbox"/> B1425	<input type="checkbox"/> B1439	<input type="checkbox"/> B1411	<input type="checkbox"/> W	<input type="checkbox"/> WH	<input type="checkbox"/> BP8MR16-BL (Blue)	<input type="checkbox"/> BP8MR16-FR (Frosted)
<input type="checkbox"/> 35W	<input type="checkbox"/> B1453 <sup>1</sup>	<input type="checkbox"/> B1478	<input type="checkbox"/> B1496	<input type="checkbox"/> B1469	<input type="checkbox"/> B1463	<input type="checkbox"/> B1416	<input type="checkbox"/> P	<input type="checkbox"/> BK	<input type="checkbox"/> BP8MR16-GR (Green)	<input type="checkbox"/> BP8MR16-SP (Spread)
<input type="checkbox"/> 50W	<input type="checkbox"/> B1454 <sup>1</sup>	<input type="checkbox"/> B1488	<input type="checkbox"/> B1483	<input type="checkbox"/> B1442	<input type="checkbox"/> B1464	<input type="checkbox"/> B1407	<input type="checkbox"/> SN	<input type="checkbox"/> SN	<input type="checkbox"/> BP8MR16-PI (Pink)	<input type="checkbox"/> BP8MR16-SF (Soft Focus)
<input type="checkbox"/> 75W	<input type="checkbox"/> B1455 <sup>1</sup>	<input type="checkbox"/> B1486	<input type="checkbox"/> B1432	<input type="checkbox"/> B1420	<input type="checkbox"/> B1465	<input type="checkbox"/> B1414	<input type="checkbox"/> CP	<input type="checkbox"/> CP	<input type="checkbox"/> BP8MR16-PU (Purple)	<input type="checkbox"/> BP8MR16-HC (Honey Comb)
<b>BALLAST</b>	<input type="checkbox"/> B1456 <sup>1</sup>	<input type="checkbox"/> B1489	<input type="checkbox"/> B1434	<input type="checkbox"/> B1422	<input type="checkbox"/> B1466	<input type="checkbox"/> B1415	<input type="checkbox"/> BZ	<input type="checkbox"/> CH	<input type="checkbox"/> BP8MR16-DL (Day Light)	<input type="checkbox"/> BP8MR16-LI (Linear)
<input type="checkbox"/> (M) Magnetic	<input type="checkbox"/> B1457 <sup>1</sup>	<input type="checkbox"/> B1479	<input type="checkbox"/> B1435	<input type="checkbox"/> B1413	<input type="checkbox"/> B1467	<input type="checkbox"/> B1404	<b>REFLECTOR</b>	<input type="checkbox"/> PB	<input type="checkbox"/> BP8MR16-YE (Yellow)	<input type="checkbox"/> BP8MR16-SOL (Solite)
<input type="checkbox"/> (E) Electronic	<input type="checkbox"/> B1458 <sup>1</sup>	<input type="checkbox"/> B1487	<input type="checkbox"/> B1484	<input type="checkbox"/> B1426	<input type="checkbox"/> B1408	<input type="checkbox"/> B1418	<input type="checkbox"/> CL	<input type="checkbox"/> BZ	<input type="checkbox"/> BP8MR16-AM (Amber)	<input type="checkbox"/> BP8MR16-CL (Clear)
<input type="checkbox"/> (TOR) Toroidal <sup>3</sup>	<input type="checkbox"/> B1459 <sup>1</sup>	<input type="checkbox"/> B1485	<input type="checkbox"/> B1436	<input type="checkbox"/> B1427	<input type="checkbox"/> B1406	<input type="checkbox"/> B1419	<input type="checkbox"/> RG	<input type="checkbox"/> CH <sup>1</sup>	<input type="checkbox"/> BP8MR16-OR (Orange)	<input type="checkbox"/> BP8MR16-UV (Ultraviolet)
<b>VOLTAGE</b>	<input type="checkbox"/> B1460 <sup>1</sup>	<input type="checkbox"/> B1491	<input type="checkbox"/> B1440	<input type="checkbox"/> B1430	<input type="checkbox"/> B1401	<input type="checkbox"/> B1433	<input type="checkbox"/> W	<input type="checkbox"/> SS <sup>2</sup>	<input type="checkbox"/> BP8MR16-RE (Red)	
<input type="checkbox"/> 120	<input type="checkbox"/> B1470 <sup>2</sup>	<input type="checkbox"/> B1480	<input type="checkbox"/> B1441	<input type="checkbox"/> B1431	<input type="checkbox"/> B1402	<input type="checkbox"/> B1417	<input type="checkbox"/> MB			
<input type="checkbox"/> 277	<input type="checkbox"/> B1471 <sup>2</sup>	<input type="checkbox"/> B1495	<input type="checkbox"/> B1421	<input type="checkbox"/> B1462	<input type="checkbox"/> B1412	<input type="checkbox"/> B1477	<input type="checkbox"/> BZ			
<b>OPTION</b>	<input type="checkbox"/> B1472 <sup>2</sup>	<input type="checkbox"/> B1490	<input type="checkbox"/> B1424	<input type="checkbox"/> B1452	<input type="checkbox"/> B1468		<input type="checkbox"/> CP			
<input type="checkbox"/> AT (Air-Shut)	<input type="checkbox"/> B1474 <sup>2</sup>	<input type="checkbox"/> B1492	<input type="checkbox"/> B1423	<input type="checkbox"/> B1437	<input type="checkbox"/> B1461		<input type="checkbox"/> SN			
	<input type="checkbox"/> B1475 <sup>2</sup>	<input type="checkbox"/> B1481	<input type="checkbox"/> B1409	<input type="checkbox"/> B1438	<input type="checkbox"/> B1403		<input type="checkbox"/> SHZ			

1 = CH - Chrome finished • 2 = SS - Stainless Steel finished • 3 = TOR -Toroidal available only in 120V

### Specifications:

#### BL4IC

WATT BALLAST VOLTAGE OPTION TRIM TYPE BAFFLE REFLECTOR TRIM/RING FILTER (1) FILTER (2)

Sample of Catalog Number: BL4IC-20W-E-B1401-W-WH-BP8MR16-BL

BAFFLE	REFLECTOR	TRIM/RING
W White	CL Chrome	WH White
P Black	RG Gold	BK Black
SN Satin Nickel	W White	SN Satin Nickel
CP Copper	MB Black	CP Copper
BZ Bronze	BZ Bronze	CH Chrome
	CP Copper	PB Polish Brass
	SN Satin Nickel	BZ Bronze
	SHZ Satin Haze	

\*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions  
subject to change without notice.

REV: ELITE LIGHTING-SPEC-05-24-2011

# 4" Low Voltage Trims

( LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10 )

Catalog Number:

Project Name:

Type:

Note:

**elite** LIGHTING

**B1451CH  
RUBY I**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1453CH  
RUBY II**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1454CH  
SAPPHIRE I**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1455CH  
SAPPHIRE II**




**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1456CH  
EMERALD I**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1457CH  
EMERALD II**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1458CH  
TOPAZ I**




**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1459CH  
TOPAZ II**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1460CH  
ONYX**



**O.D.:** 4-7/8"  
**FINISH TRIM:** CH (CHROME)

**B1470SS  
ADJ. STAINLESS STEEL GIMBAL TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1471SS  
STAINLESS STEEL LENSED TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1472SS  
STAINLESS STEEL EYEBALL TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1474SS  
ADJ. STAINLESS STEEL SQUARE GIMBAL TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1475SS  
STAINLESS STEEL SQUARE EYEBALL TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1476SS  
ADJ. STAINLESS STEEL SQUARE EYEBALL TRIM**



**O.D.:** 4-7/8"  
**FINISH TRIM:** SS (STAINLESS STEEL)

**B1496SN  
SQUARE BAFFLE W/ SQUARE TRIM RING**



**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**elite** LIGHTING

Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions  
subject to change without notice.

REV: MAXLUME-SPEC-05-26-2011

4"

# Low Voltage Trims

( LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10 )

Catalog Number:


Project Name:

Type:


Note:


**B1478SN-SN  
STEPPED BAFFLE (35° TILT)**


**BAFFLE FINISH:**  
W, P, SN, CP, BZ


**RING FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1479CL-WH  
REFLECTOR (35° TILT)**


**REFLECTOR FINISH:**  
CL, RG, MB, W, CP, SN


**RING FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1494WH-BLUE  
DESIGNER SQUARE STEP LITE**


**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB




**GLASS FINISH:**  
BLUE, PEACH, GREEN,  
FROSTED

**B1485W-WH  
EYEBALL (47° TILT)**


**AVAILABLE COLOR COMBINATIONS:**  
CP-CP, SN-SN, W-WH,  
P-WH, P-BK

**B1488CP  
SURFACE ADJUSTABLE (90° TILT, 359° ROT)**


**RING FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1486WH  
FULLY ADJUSTABLE (75° TILT, 359° ROT)**


**RING FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1489W-WH  
ADJ. PINHOLE W/ BAFFLE (35° TILT)**

**AVAILABLE COLOR COMBINATIONS:**  
W-WH, P-WH

**B1487WH  
ADJUSTABLE SPOT (40° TILT)**




**RING FINISH:**  
WH, BK

**B1483WH  
SLOT APERTURE (35° TILT)**

**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1480WH  
FULLY ADJUSTABLE (35° TILT, 359° ROT.)**

**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1484P-WH  
FULLY ADJ. W/ BAFFLE (35° TILT, 359° ROT.)**


**AVAILABLE COLOR COMBINATIONS:**  
W-WH, P-WH, P-BK,  
CP-CP, SN-SN, BZ-BZ

**B1481WH  
ADJUSTABLE GIMBAL (40° TILT)**

**TRIM FINISH:**  
WH, BK, SN, CP, CH,  
PB, BZ

**B1495CL-SN  
SEMI-FROSTED SHOWER TRIM**


**REFLECTOR FINISH:**  
CL, RG, W, MB, CP, SN

**RING FINISH:**  
WH, BK, SN, CP, CH, PB, BZ

**B1491P-WH  
PINHOLE WITH BAFFLE**

**AVAILABLE COLOR COMBINATIONS:**  
CP-CP, SN-SN, W-WH,  
P-WH, P-BK

**B1492WH-BLUE  
METROPOLITAN ICE LITE**

**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB

**GLASS FINISH:**  
BLUE, PEACH, GREEN,  
CLEAR, AMBER, FROSTED

**B1490WH-PEACH  
METROPOLITAN ICE LITE**

**TRIM FINISH:**  
WH, BK, SN, CP, CH, PB

**GLASS FINISH:**  
BLUE, PEACH, GREEN,  
CLEAR, AMBER, FROSTED



Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions  
subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

4"

# Low Voltage Trims

( LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10 )

Catalog Number:


Project Name:

Type:


Note:


**B1401CP-CP**  
**STEPPED BAFFLE**



**BAFFLE FINISH:**  
 W, P, SN, CP, BZ


**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1402CP-WH**  
**REFLECTOR (35° TILT)**

**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN, BZ


**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1463RG-WH**  
**ADJUSTABLE ANGLE-CUT REFLECTOR**


**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB

**B1464CP-CP**  
**ADJUSTABLE ANGLE-CUT BAFFLE**

**BAFFLE FINISH:**  
 W, P, SN, CP


**RING FINISH:**  
 WH, BK, SN, CP, CH, PB

**B1465CL-WH**  
**ADJUSTABLE ANGLE-CUT PINHOLE**


**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN


**RING FINISH:**  
 WH, SN, CP

**B1466CL-WH**  
**ADJUSTABLE ANGLE-CUT SLOT APERTURE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB

**B1467CL-WH**  
**ADJUSTABLE LENSED WALL WASH**


**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**TRIM COVER:**  
 WH, BK

**B1411WH**  
**SLOT APERTURE (35° TILT, 179° ROT)**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1403CP**  
**ONE PIECE SLOT APERTURE (35° TILT)**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1416P-WH**  
**BAFFLE WALL WASH**


**BAFFLE FINISH:**  
 W, P, SN, CP, BZ


**WALL WASH COVER:**  
 WH, BK

**B1407CL-WH**  
**REFLECTOR WALL WASH**


**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN


**WALL WASH COVER:**  
 WH, BK

**B1414W-WH**  
**PINHOLE WITH BAFFLE**

**AVAILABLE COLOR COMBINATIONS:**  
 CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

**B1415CL-WH**  
**PINHOLE WITH REFLECTOR**

**AVAILABLE COLOR COMBINATIONS:**  
 CL-WH, CL-SN, RG-WH, MB-WH, W-WH

**B1404P-WH**  
**EYEBALL (47° TILT)**

**AVAILABLE COLOR COMBINATIONS:**  
 CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

**B1418P-WH**  
**ADJ.PINHOLE W/ EYEBALL (35° TILT)**

**AVAILABLE COLOR COMBINATIONS:**  
 W-WH, P-WH, P-BK, P-PB, W-CH

**B1412CH**  
**FULLY ADJUSTABLE (35° TILT, 359° ROT.)**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ



 Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
 Tel: 323-888-1973 • Fax: 323-888-1977

 Specifications and Dimensions  
 subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011



4"

# Low Voltage Trims

( LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10 )

Catalog Number:


Project Name:

Type:

Note:

**B1468W-WH**  
 FULLY ADJ. W/ BAFFLE (35° TILT, 359° ROT.)



**AVAILABLE COLOR COMBINATIONS:**  
 CP-CP, SN-SN, W-WH,  
 P-WH, P-BK, BZ-BZ

**B1461SN**  
 ADJUSTABLE GIMBAL (40° TILT)



**TRIM FINISH:**  
 WH, BK, SN, CP,  
 CH, PB, BZ

**B1408WH**  
 FULLY ADJUSTABLE (75° TILT, 359° ROT.)


**TRIM FINISH:**  
 WH, BK, SN, CP,  
 CH, PB, BZ


**B1406CP**  
 SURFACE ADJUSTABLE (90° TILT, 359° ROT.)


**TRIM FINISH:**  
 WH, BK, SN, CP,  
 CH, PB, BZ

**B1413P-SN**  
 PULL DOWN ADJUSTABLE


**BAFFLE FINISH:**  
 W, P, SN, CP, BZ


**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1419BK**  
 ADJUSTABLE SPOT (40° TILT)


**TRIM/RING FINISH:**  
 WH, BK, SN


**B1433P-WH**  
 ADJUSTABLE PINHOLE BAFFLE (15° TILT)


**AVAILABLE COLOR COMBINATIONS:**  
 W-WH, P-WH

**B1417W-WH**  
 METAL STEPPED BAFFLE


**BAFFLE FINISH:**  
 W, P, SN, CP, BZ

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1426CL-WH**  
 THE ILLUMINATOR II



**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN

**B1427CL-WH**  
 THE ILLUMINATOR



**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN

**B1477CL-WH**  
 CROSSBLADE REFLECTOR



**REFLECTOR FINISH:**  
 CL

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1462CL-WH**  
 SEMI-FROSTED SHOWER TRIM



**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1452CL-WH**  
 CLEAR LENS SHOWER TRIM



**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1437WH**  
 SMOOTH FROST SHOWER LITE



**REFLECTOR FINISH:**  
 CL

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1438WH**  
 DESIGNER POINT SHOWER LITE


**REFLECTOR FINISH:**  
 CL, RG, W, MB, CP, SN

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**B1439WH**  
 SMOOTH FROST DOME SHOWER LITE


**REFLECTOR FINISH:**  
 CL

**RING FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
 Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions  
 subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011

4"

# Low Voltage Trims

( LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10 )

Catalog Number:


Project Name:

Type:

Note:


**B1436WH**  
**CYLINDER LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ


**GLASS FINISH:**  
 WHITE, PINK, BLUE, GREEN

**B1434WH / B1435WH**  
**STRIPE WALL WASH LITE**
**B1434WH**

**B1435WH**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 CRYSTAL/FROST

**B1440WH-PINK**  
**TULIP LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 TEAL, PINK, LIME, BLUE

**B1441WH-LIME**  
**DESIGNER WALL WASH LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 TEAL, PINK, LIME, BLUE

**B1424WH-RED**  
**METROPOLITAN HONEY LITE**



**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ


**GLASS FINISH:**  
 BLUE, RED, WHITE, GREEN

**B1420WH-GREEN**  
**METROPOLITAN MOON LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ


**GLASS FINISH:**  
 BLUE, PEACH, GREEN, CLEAR,  
 AMBER, FROSTED

**B1425WH-AMBER**  
**METROPOLITAN STEP LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ


**GLASS FINISH:**  
 BLUE, PEACH, GREEN, CLEAR,  
 AMBER, FROSTED

**B1442WH-PEACH**  
**DESIGNER MOON LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 BLUE, PEACH, GREEN,  
 FROSTED

**B1431WH**  
**CRYSTAL STRIPE LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 CRYSTAL/FROST

**B1432WH**  
**WALL WASH FROST LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 WHITE, PINK, BLUE, GREEN

**B1421WH-FROSTED**  
**MINI-STEP LENS LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 FROSTED

**B1423WH-WHITE**  
**METROPOLITAN OPAL LENS LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 CRYSTAL, WHITE, FROSTED

**B1409WH-BLUE**  
**PYRAMID GLASS LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 TEAL, PINK, LIME, BLUE

**B1469WH-BLUE**  
**DESIGNER STEP LITE**


**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 BLUE, PEACH, GREEN, FROSTED

**B1422WH-FROSTED**  
**METROPOLITAN ICE LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH, PB, BZ

**GLASS FINISH:**  
 BLUE, PEACH, GREEN, CLEAR,  
 AMBER, FROSTED

**B1430WH**  
**CRYSTAL ROSE LITE**

**TRIM FINISH:**  
 WH, BK, SN, CP, CH,  
 PB, BZ

**GLASS FINISH:**  
 CRYSTAL



 Submittal form is available @ [www.iuseelite.com](http://www.iuseelite.com)  
 Tel: 323-888-1973 • Fax: 323-888-1977

 Specifications and Dimensions  
 subject to change without notice.

REV: MAXLUME-SPEC-05-26-2011