


8741 Large Diameter Series

APOLLOXPRESS® Press End Copper Companion Flange 125lb C (2 ½" through 4")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







DESCRIPTION

The APOLLOXPRESS® 8741 Large Diameter Press 125lb Companion Flange features a Lead-Free dezincification resistant copper body, a patented stainless-steel solid cross-section Grab Ring, a Nylon Separation Ring and an EPDM O-Ring. The black powder coating provides separation of dissimilar metals preventing electrolysis. Our Large Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Black powder-coated steel flange base
- Lead-Free Construction
- Leak-Before-Press Technology
- Visual element, Break Away Band (Pat. Pending)
- Compatible with XL-C™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)

APOLLOXPRESS

- Large Diameter Sizes 2 1/2", 3" & 4"
- Model 8741, 125lb Companion Flange

STANDARD MATERIALS

Part Name	Material			
Body	UNS C12200 Copper			
Grab Ring	304 / 306 Stainless Steel			
Spacer Ring	Nylon 66			
Flange Base	Black Powder-Coated Steel			
O-Ring	EPDM			
Lubrication	Silicone, ANSI/NSF-61 Listed			

DIMENSIONS

			(lb.)					
Item No.	Description	Α	В	C*	Height	Width	Depth	Weight
10061761	8741 2½	7.00	3.62	1.90	3.62	7.00	7.00	3.92
10061767	8741 3	7.50	3.61	2.10	3.61	7.50	7.50	5.32
10061736	8741 4	9.00	3.82	2.50	3.82	9.00	9.00	7.52

^{*} Tolerance +/- .02"

Elkhart Products Corporation

8741 LD XPRESS SPEC SHEET REV D

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.

