

807R Small Diameter Series

APOLLOXPRESS® Press End **Reducing Copper Elbow** 90° CxC (3/4" x 1/2" through 1" x 3/4")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







DESCRIPTION

The APOLLOXPRESS® 807 Small Diameter Press Reducing Elbow features a Lead-Free dezincification resistant copper body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS

- Small Diameter Sizes 3/4" x 1/2" through 1" x 3/4"
- Model 807R, 90° Elbow C x C

STANDARD MATERIALS

Part Name	Material					
Body	UNS C12200 Copper					
O-Ring	EPDM					
Lubrication	Silicone, ANSI/NSF-61 Listed					

DIMENSIONS

		Dimension (in.)							(lb.)		
Item No.	Description	Α	В	C*	D**	E*	F**	Height	Width	Depth	Weight
10066101	807 34x1/2 CxC	2.58	3.67	0.93	1.03	0.81	2.25	3.67	2.58	1.24	0.27
10066099	807 1x½ CxC	2.97	4.43	0.92	1.31	0.81	2.88	4.43	2.97	1.49	0.41
10066083	807 1x¾ CxC	2.97	4.27	0.92	1.31	0.85	2.68	4.27	2.97	1.49	0.43

^{*} Tolerance +/- .045"

Note:

These fittings are crimped two-piece construction.


Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181

www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this

specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.





^{**} Tolerance +.09 / -.03