

SUBMITTAL SHEET

8707-4-R Small Diameter Series

APOLLOXPRESS® Press End Copper/Brass Elbow

Reducing 90° CxM (N.P.T.) (½" x ¾" & ¾" x ½")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	

APOLLOXPRESS
YOUR SINGLE SOURCE SOLUTION FOR PRESS TECHNOLOGY



DESCRIPTION

The APOLLOXPRESS® 8707-4-R Small Diameter Press Elbow features a Lead-Free dezincification resistant copper and brass body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Male N.P.T. per ANSI/ASME B1.20.1
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: 0°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS

- Small Diameter Sizes ½" x ¾" & ¾" x ½"
- Model 8707-4-R, Reducing Elbow with Male N.P.T.

STANDARD MATERIALS

Part Name	Material
Elbow Body	UNS C12200 Copper
Brass Body	UNS C27451 Brass
O-Ring	EPDM
Lubrication	Silicone, ANSI/NSF-61 Listed


DIMENSIONS

Item No.	Description	Dimension (in.)								(lb.)
		A	B	C*	D**	E*	Height	Width	Depth	
10066576	8707-4 ½x¾ CxM	2.03	3.62	0.76	0.74	3.15	3.62	2.03	1.05	0.36
10066577	8707-4 ¾x½ CxM	2.58	3.94	0.93	1.03	3.32	3.94	2.58	1.24	0.35

* Tolerance +/- .05"

** Tolerance +.09 / -.03

Note:
These fittings are crimped
two-piece construction.



Elkhart Products Corporation
1255 Oak Street, Elkhart, IN 46514
www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.