

804 Small Diameter Series

APOLLOXPRESS® Press End Brass Male Adapter CxM (½" through 2")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







DESCRIPTION

The APOLLOXPRESS® 804 Small Diameter Press Male Adapter features a Lead-Free dezincification resistant brass body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS

- Small Diameter Sizes ½" through 2"
- Model 804, Male Adapter.

STANDARD MATERIALS

Part Name	Material				
Body	UNS C27451 Brass				
O-Ring	EPDM				
Lubrication	Silicone, ANSI/NSF-61 Listed				

DIMENSIONS

			(lb.)					
Item No.	Description	Α	В	C*	Height	Width	Depth	Weight
10075806	804 ½ CxM	1.92	0.93	0.76	0.93	1.92	0.93	0.13
10075808	804 ¾ CxM	2.15	1.26	0.92	1.26	2.15	1.26	0.21
10075844	804 1 CxM	2.39	1.50	0.92	1.50	2.39	1.50	0.31
10075810	804 1¼ CxM	2.39	1.71	1.04	1.71	2.39	1.71	0.35
10075812	804 1½ CxM	2.86	2.13	1.31	2.13	2.86	2.13	0.58
10075814	804 2 CxM	2.97	2.60	1.59	2.60	2.97	2.60	0.80

B REF. - C - A REF. -

Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.



^{*} Tolerance +/- .045"