

OIL TANK VALVE (OILTANK)

Applications:

Brass valves for use in oil tank applications.


- CSA Certified to 200 PSI for use with Fuel ,Oil.
- **TEMPERATURE:** -40°F to +149°F
-40°C to +65°C



**MALE PIPE
TO
MALE PIPE**

PART No.	Pipe	Pipe	W.O.G.
1122-DC	1/2	3/8	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C



**MALE FLARE
TO
MALE PIPE**

(Complete with flare nut 40-6)

PART No.	Tube	Pipe	W.O.G.
1048-6D	3/8	1/2	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C



**1/4 TURN
BALL VALVE
MALE PIPE TO
MALE PIPE**

PART No.	Pipe	Pipe	W.O.G.
BV1122-DC	1/2	3/8	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C



**1/4 TURN
BALL VALVE
MALE FLARE TO
MALE PIPE**

(Complete with flare nut 40-6)

PART No.	Tube	Pipe	W.O.G.
BV1048-6D	3/8	1/2	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C



**1/4 TURN
90° BALL VALVE
MALE PIPE
TO
MALE PIPE**

PART No.	Pipe	Pipe	W.O.G.
BV1199-DC	1/2	3/8	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C



**1/4 TURN
90° BALL VALVE
MALE FLARE TO
MALE PIPE**

(Complete with flare nut 40-6)

PART No.	Tube	Pipe	W.O.G.
BV1049-6D	3/8	1/2	200
BV1049-8D	1/2	1/2	200

CSA Certified to 200 PSI for use with Fuel ,Oil.
Temperature: -40°F to +149°F
-40°C to +65°C