

# GAS-FLO 3/8" NATURAL GAS / PROPANE GAS OUTLETS (NGO-2)

Applications:



Overall Dimensions of NGO-2  
OUTLET COVER measures:  
5-3/4" H x 3-1/2" W x 2-1/2" D

### SAFETY FEATURE

**\* Connect / Disconnect are Denied While Gas is Flowing.**



PART No.	Description
NG-OUTLET-NCN	Gas Outlet with Stainless Cover (No Coupler or Nipple)

### PART No.: NGO-2 (ABS Cover)

- U.V. / SHOCK RESISTANT ABS OUTLET COVER.
- 3/8 C.S.A. CONVENIENCE OUTLET (VALVE WITH COUPLER).
- APPLIANCE ATTACHMENT (NIPPLE).
- GAS-ON LOCKING DEVICE
- OUTLET DUST PLUG.
- STANDOFF SPACERS.
- MOUNTING BRACKET.

**THERMAL PROTECTION  
DEVICE SHUTS  
OFF FLOW OF GAS  
AT +250°F, +121°C**



Hose Assembly Length Restrictions May Apply:  
Check with Local Jurisdictions

• Natural Gas CSA Rated 80,000 BTU/H @ 0.5 PSIG with 0.6" wc pressure drop.  
Propane Gas CSA Rated 125,000 BTU/H @ 0.6" wc pressure drop.

PART No.	Description
NGO-2	Gas Outlet with White ABS Housing
NGO-2HT	White - With Hanger Tab Rack Package

**Gas Hose Assemblies Sold Separately**

**CAUTION: Gas Outlets are to be installed by Licensed Gas fitters only.**