



Representative Image

Catalog No. TG3325**Description: 400A 3P GD N1 240V FUSIBLE****UPC No 783164008593****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG3325

Descriptors

Category

General Duty

Specifications

Amperage	400 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 3-ph	50
240 Vac, Time Delay, 3-ph	100
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	49.4
Depth	8.7
Width	21.6
Weight	107

