



Representative Image

**Catalog No. TH4365C****Description: 400A 3P HD N1 600V FUSIBLE CSA****UPC No 783164422467****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Suitable for use as service equipment when installed in accordance with the Canadian Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH4365C

**Descriptors**

Category	Heavy Duty
GO Schedule	S1

**Specifications**

Voltage	600 AC
Amperage	400 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	CSA SE Rated
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 3-ph	50
240 Vac, Time Delay, 3-ph	125
480 Vac, NEC Std, 3-ph	100
480 Vac, Time Delay, 3-ph	250
600 Vac, NEC Std, 3-ph	125
600 Vac, Time Delay, 3-ph	350
250 Vdc	50
GSA Compliance	Yes

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	53.9
Depth	8.3
Width	22.9
Weight	132

**by ABB**

