



Representative Image

Catalog No. THQLQ204020

Description: QUAD 20A/1P & 40A/2P & 20A/1P 120/240V

UPC No 783164681451

Home > Circuit Breakers > Residential Circuit Breakers > Q Line

Same panel space, twice the circuits. Tandems and Quads are code compliant and compatible with new and existing single phase ABB and GE by ABB PowerMark™ load centers with or without wing stabs.

Descriptors

Category	Q Line
Product Line	Q-Line (Plug-In)
GO Schedule	R5

Specifications

Interrupting Capacity Rating	10 kAIC
Voltage	120/240 V
Trip Style	Non-Interchangeable
Frame Type	Q-Line
Amperage	20-40-20 A
System Voltage	120 Vac 120/240 Vac
Poles	2-1p+1-2p
Trip Function	LI
Continuous Current Rated	Standard
120 Vac Interrupting Rating	10 KAIC
120/240 Vac Interrupting Rating	10 KAIC
Suitable for Reverse Feed	Yes
Wire Range (Cu/Al)	(2) # 14-8 CU/ #12-8 AL, #8-4 CU for 40a 2/pole
Long Time	Fixed
Instantaneous	Fixed
Protective Relays	No
Current Metering	No
Special Markings	HACR SWD

Classifications

UL File #	E11592
-----------	--------