







Vapour Proof



Vapour Proof Kit



Replacement Lens



Order code	Description	Color	Material	Dimensions (in.)				
				A	B	C	D	E
Vapour Proof Kit								
35552	VPR PROOF HOUSING SHALLOW KIT 48L	White	Fiberglass	7-5/8	5-5/8	2-13/16	49-59/64	38-3/4
35553	VPR PROOF HOUSING DEEP KIT 96L	White	Fiberglass	7-5/8	5-5/8	2-13/16	97-15/16	86-3/4

Order code	Description	Color	Material	Pattern	Outside height (in.)	Outside length (in.)	Outside width (in.)
Replacement Lens							
35217	VPR PROOF LENS ACR CL SMTH 49-5/8L	Clear	Acrylic	Smooth	2-11/16	49-5/8	7-3/4
56004	VPR PROOF LENS ACR CL CRP 49-11/16L	Clear	Acrylic	Crepe	2	49-11/16	6-1/2
57072	VPR PROOF LENS ACR CL CRP 49-11/16L	Clear	Acrylic	Crepe	3	49-11/16	7-3/8
35749	VPR PROOF LENS ACR CL CRP 49-15/16L	Clear	Acrylic	Crepe	2-5/8	49-15/16	7-5/8
35212	VPR PROOF LENS ACR CL CRP 50-7/8L	Clear	Acrylic	Crepe	2	50-7/8	6-1/2
35208	VPR PROOF LENS ACR CL CRP 52L	Clear	Acrylic	Crepe	2-5/8	52	7-1/2
35209	VPR PROOF LENS POLY CL SMTH 52L	Clear	Polycarbonate	Smooth	2-5/8	52	7-1/2
35551	VPR PROOF LENS ACR CL CRP 97-3/4L	Clear	Acrylic	Crepe	2-5/8	97-3/4	7-1/2
35751	VPR PROOF LENS ACR CL CRP 97-3/4L DEEP	Clear	Acrylic	Crepe	3	97-3/4	6-1/2
35211	VPR PROOF LENS ACR CL CRP 102L	Clear	Acrylic	Crepe	2-5/8	102	7-1/2

Accessory


Order code	Description	Color	Material
Replacement Clip			
12866	VPR PROOF CLIP POLY WH	White	Polycarbonate





Sockets & Accessories


CFL Sockets



Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38221	HORIZONTAL SNAP-IN MNT	2G11	600	75	10/2 000
38222	HORIZ 90D BOTTOM SNAP-IN MNT	2G11	600	75	10/2 000
38108	7-9WT VERT MNT 4 HOLE METAL/CLIP	G23 / G23-2	600	75	20/2 000
11588	CF13-HSM HORIZ BOTTOM SCREW MT	G23 / GX23	600	75	10/250
38127	18WT 4-PIN HORIZONTAL SCR MNT	G24q-2	600	75	10/2 000
11633	26WT VERT TOP/BOTTOM SCR MNT	G24d-3	600	75	10/500
38132	26WT VERTICAL 4 HOLE SCREW MN	G24d-3	600	75	10/2 000
38121	13WT 4-PIN HORZ SCR MNT 2 HOL	G24q-1	600	75	10/2 000
38064	SKT42 13-42W 4PIN UNIV.SOCKET	G24q-1/G24q-2 /G24q-3 /G24q-4	600	75	1/1 000
38113	13 WT VERTICAL MOUNT SNAP-IN	GX23	600	75	10/2 000
38112	13 WT VERTICAL MOUNT 4 HOLE	GX23 / GX23-2	600	75	N/A
38133	26WT 4-PIN VERT 4 HOLE SCR MN	GX24q-3	600	75	1/2 000
38136	26WT 4-PIN HORIZONTAL SCREW M	GX24q-3	600	75	10/2 000



Fluorescent Sockets



Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38034	7-9 WT VERTICAL MOUNT	G23 / G23-2	600	75	250/2 500
38017	T8/T12 TALL PRF w/CN SCR/SLDE	G13	600	660	10/300
38197	T8/T12 TALL PRF SNAP-IN SHUNTED	G13	600	660	250/2 500
38240	T8/T12 LOW PRF SLIDE MNT STD	G13	600	660	10/1 000
38241	T8/T12 LOW PRF SLIDE MNT SHUNTED STD	G13	600	660	10/1 000
38242	T8/T12 TALL PRF SLIDE MNT STD	G13	600	660	10/1 000
38243	T8/T12 LOW PRF U SLIDE MNT STD	G13	600	660	1/10
58791	T8/T12 ROTARY SHUNTED TALL LOCKABLE	G13	600	660	10/500
58792	T8/T12 ROTARY SHUNTED LOW LOCKABLE	G13	600	660	10/500
66006	T8/T12 LOW PRF SNAP-IN SHUNTED	G13	600	660	10/1 000
38003	T5 REAR SNP MNT LOCK w/SPG PLT	G5	600	120	10/2 000



0.76" - 19.30 mm



38004

1.26" - 32.00 mm

0.83" - 21.08 mm



38245

0.96" - 24.38 mm

1.37" - 35.00 mm



38022

2.11" - 53.59 mm

1.37" - 35.00 mm



38023

2.09" - 53.09 mm

1.57" - 39.88 mm



38024

0.83" - 21.08 mm

1.56" - 39.62 mm



38025

1.17" - 29.72 mm

1.12" - 28.45 mm



38026

2.24" - 56.90 mm

1.31" - 33.27 mm



38027

2.42" - 61.47 mm

1.31" - 33.27 mm



38030

2.04" - 51.82 mm

1.22" - 31.00 mm



38031

1.66" - 42.16 mm

1.37" - 35.00 mm



59800

1.57" - 40.00 mm

1.27" - 32.26 mm



38020

1.90" - 48.26 mm

1.31" - 33.27 mm



38021

1.91" - 48.51 mm

Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38004	T5 MED SNP/SCR MNT ROT. LOCK	G5	600	120	10/5 000
38245	T5 SNAP-IN or SCREW MNT STD	G5	600	120	10/1 000
38022	T12 HO VERT SPNG END 9" LEADS	R17d	600	660	N/A
38023	T12 HO VERT STAT END 9" LEADS	R17d	600/1 000	660	10/500
38024	SK82 SNAP-IN STATIONARY END	R17d	600	660	1/500
38025	T12 HO SNPIN/SPRING END R17d	R17d	600	660	1/500
38026	T12 HO FIX END SLD/LCK-ON MNT	R17d	600	660	10/500
38027	T12 HO PLNG END SLD/LCK-ON MNT	R17d	600	1000	10/500
38030	SK900 HORIZONTAL STATION. END	R17d	600	660	10/500
38031	SK901 HORIZONTAL SPRING END	R17d	1000	660	10/500
59800	T8/T12 SPRING END/SLIDE ON	R17d	600	660	10/200
38020	T8/T12 SLIML STAT END SLD MNT	Fa8	600	660	10/200
38021	T8/T12 SLIML PLNG END SLD MNT	Fa8	600	1 000	10/200




HID Sockets



Order code	Description	Base	Volts	Watts	Case qty (inner/master)
			(V)	(W)	
38062	4KV 24" SEW-2 LEADS PULSE RTD	E26	600	660	1/250
38168	4KV 2MALE SCR MNT 12"SEW-1LEA	E26	600	660	1/250
10983	PORC MOG 1/2" DIE CAST CAP	E39	600	1 500	1/50
68452	4KV MOGUL E39 12" MOUNTING SCREWS	E39	600	1 500	1/75



Halogen Sockets



Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38051	G4 BACK ENTRY 12" LEADS	G4	24	100	10/200
62187	DF-05 GU-10/GZ-10 BASE (TAL) LAMPHOLDER	GU10	250	1 000	N/A
38043	PAR CONNECTOR MOGUL END PRONG	GX16d	125	1 000	1/200
38045	GX5.3/GU5.3 (MR16) BACK ENTRY 6"LEA	GX5.3/GU5.3	250	1 000	10/250
38049	GX5.3/GU5.3 (MR16) SIDE ENTRY 12"LEADS	GX5.3/GU5.3	24	100	1/50
38054	RSC BRACKET MOUNT(SINGLE SOCK	R7s	250	1 000	10/200
38055	RSC 119MM ON BRACKET(DBL SOCK	R7s	250	1 000	25/200



Incandescent Sockets



Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38072	ADJ 3.5" TO 4.75" SCR TERM	E12	125	75	10/500
38075	W/SHOULDER & RING 6" LEADS	E12	125	75	10/250
38076	1-1/2" OVERALL 20" TEW LEADS	E12	125	75	10/250
38206	Z-TYPE BRACKET 9.5" TEW NPT	E12	125	75	10/250
38079	PHEN 1/2" HKY 12" LEADS ALSS	E26	250	660	10/250
69376	PORC 1/2" HKY 24" LEADS ALSS	E26	250	660	10/250
38083	PORC 1/2" HKY SCR TERM ALSS	E26	250	660	10/250
38085	MED PORC ALUMINUM SCREW SHELL	E26	250	660	1/250
38084	PORC SNAP-IN 9" EXL LEADS	E26	250	660	10/250
38088	2 PC PHEN W/HUSK SCR TERM	E26	250	660	10/250





Order code	Description	Base	Volts (V)	Watts (W)	Case qty (inner/master)
38086	MED PORC NICKEL PLATED SCREW SHELL	E26	250	660	10/250
38100	FRONT MNT SNAP-IN SCR TERM	E26	250	660	10/250
38103	BACK SNAP-IN W/24" 14GA LEADS	E26	250	660	1/250
38105	2" CC 2 HOLE FLANG SCR TERM	E26	250	660	10/250
38209	2PC KEYLESS W/SCREW TERMINALS	E26	250	660	10/250
38088	2 PC PHEN W/HUSK SCR TERM	E26	250	660	10/250




Battery

- Full particle tank formation - Delivers 100% capacity on first cycle
- Immobilized electrolyte - non-spillable, useable in any position, and maintenance free.
- Rechargeable - provides hundreds to thousands of recharge cycles (depending on depth of discharge)
- Extended life span - batteries are designed to last 3 to 5 years in standby applications at 25°C under JIS and Eurobat standards.
- Superior shelf life - battery can be stored for over of 12 months at 20°C.
- Fire alarm, security systems and emergency lighting equipment stanby use.
- Emergency lighting equipment.



Terminal schematics



Order code	Description	Volts (V)	Rated capacity (Ah) *	Weight (lb) (kg)	Terminal type	Max. charging current (A)	Case qty (master)
Figure A							
Length : 2 3/4 in. (70 mm) Width : 1 27/32 in. (47 mm) Height** : 3 31/32 in. (101 mm)							
57338	BATTERY/6V/5AH/0.188/TABS (BATPM6-5)	6	5.0	1.65 0.74	F0-02/F0-03	1.50	20
Figure B							
Length : 5 29/32 in. (150 mm) Width : 1 11/32 in. (34 mm) Height** : 3 11/16 in. (94 mm)							
57336	BATTERY/6V/7.2AH/0.250/TABS (BATPM6-7.2)	6	7.2	2.45 1.12	F0-02/F0-03	2.16	10
Length : 5 15/16 in. (151 mm) Width : 2 in. (51 mm) Height** : 3 11/16 in. (94 mm)							
57339	BATTERY/6V/12AH/0.250/TABS (BATPM6-12)	6	12.0	3.70 1.68	F0-02/F0-03	3.60	10
Figure C							
Length : 3 27/32 in. (98 mm) Width : 2 7/32 in. (56 mm) Height** : 4 21/32 in. (118 mm)							
57807	BATTERY/6V/8.5AH (BATPM6-8.5-F0-01)	6	8.5	3.52 1.60	F0-01/F0-02	2.55	10
Figure D							
Length : 3 17/32 in. (90 mm) Width : 2 3/4 in. (70 mm) Height** : 4 in. (101 mm)							
63623	BATTERY/12V/4.5AH (BAT12-4.5)	12	4.5	3.61 1.64	F0-01/F0-02	1.35	12
Figure E							
Length : 5 15/16 in. (151 mm) Width : 2 9/16 in. (65 mm) Height** : 3 3/4 in. (95 mm)							
57337	BATTERY/12V/7.2Ah/0.188/TABS (BAT12-7.2)	12	7.2	4.80 2.18	F0-02/F0-03	2.16	5
Figure F							
Length : 5 15/16 in. (151 mm) Width : 3 27/32 in. (98 mm) Height** : 3 11/16 in. (94 mm)							
57804	BATTERY/12V/12AH/ (BAT12-12-F0-02)	12	12.0	8.82 4.00	F0-02/F0-03	3.60	4
Figure G							
Length : 7 23/32 in. (196 mm) Width : 5 1/8 in. (130 mm) Height** : 6 13/32 in. (163 mm)							
57341	BATTERY/12V/32AH (BAT12-32)	12	32.0	22.20 10.06	RT-01 / FP-07	9.60	1
Length : 7 3/4 in. (197 mm) Width : 5 3/16 in. (132 mm) Height** : 6 1/2 in. (165 mm)							
57335	BATTERY/12V/35AH (BAT12-35)	12	35.0	23.10 10.50	RT-01 / FP-07	10.50	1

NOTE: * 20 hr to 1.75V/cell ** Container height

Luminaire Disconnect

Features

- Push-wire connection technology
- Up to 12 AWG (solid or stranded) for power input wiring
- 2 conductors per pole on power input side
- Color coding and/or marking
- Male/female are mechanically keyed
- Compact and sleek design
- UL 94 V-0 flammability rating



Completely touch-proof
in the unmated position

Order code	Description	Electrical specs	Rated Temperature	Case qty
58869	Luminaire Disconnect	600 V - 6 A	105°C	500

