



# Specification Sheet

## 600V Class Energy Efficient Commercial General Purpose Distribution Transformers

### HPS Express™

**Winding Material** Aluminum

**Rating** Ratings from 15 to 200 kVA single phase and 15 to 300kVA three phase

**Voltage** Primary voltage: 600, 480 Volt

**Frequency** 60 Hertz

**Core** High grade non-aging, fully processed silicon steel laminations or better

**Coil** Aluminum windings, with terminations brazed, welded or bolted.

**Termination** Front accessible separate grounding, separate high and low voltage terminations with either lugs or pads.

**Enclosure** Type 1 in ANSI 61 Grey painted finish. (Type 2 when optional sprinkler hood kits are installed)

**Mounting** Floor mounting for all units and wall mounting for units under 600 Lbs.

**Warranty** 1 year

### Approvals and Standards



CSA Certified, UL Listed

### Features and Benefits

Meets efficiency levels in accordance with U.S. DOE 10 CFR Part 431(TP1) and Canadian CSA C802.2 as referenced SOR/94-651 at 35% of rated load.

Efficiencies are calculated under a linear load profile.

Ideally suited for commercial applications and provide an efficient and economical solutions.

Lugs up to 300kVA

### Options

Sprinkler hood kit (floor mount only)

Wall mount brackets up to 75 kVA

*Data subject to change without notice. Please visit [www.hammondpowersolutions.com](http://www.hammondpowersolutions.com) for the most current data.*