



UPC Code: 07847781464 Country Of Origin: Mexico

LB240-GF

Brand Features

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. GFCI circuit breakers offer advanced technology to help protect against electrical shock due to ground faults. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status at-a-glance.

*For applications up to 60A when using copper wire; or 50A when using aluminum wire

Item Description

Branch Circuit Breaker, GFCI 2-Pole 40A 120/240V, 10Ka Interrupt Rating

Technical Information

Product Features Operating Temperature: 0°C to 40°C

Electrical Specifications Amperage: 40 A Pole: 2 Short Circuit Current Rating: 10 KA Type: GFCI Voltage: 120/240 VAC Standards & Certifications CSA-C22.2 No. 5-02: Yes EMC Compatibility: Yes FCC: Yes RoHS: Yes UL 489: Yes UL 943: Yes

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

