

DEFINITY™ A19 and G25

FEATURES

- Dimmable to 5 % of light on most dimmers
- 8 watts – up to 84 % more efficient than comparable 40/50 watt incandescent lamp (A19/G25 versions)
- Maintenance free operation, lasts up to 50 times longer than conventional lighting
- RoHS compliant – contains no mercury or lead
-  Visit our website for a complete listing of all DEFINITY ENERGY STAR qualified products

G25 { MOL = 4 1/8 in. (119 mm)
Dia. = 3 1/2 in. (80 mm)

A19 { MOL = 4 7/8 in. (111.5 mm)
Dia. = 2 3/8 in. (58.5 mm)



CERTIFICATIONS



ENVIRONMENT



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)	Dimmable (Yes/No)
A19											
61572	DFN 19 W27 120	8	E26	120	2 700	85	50 000	395	24	40	Y
61571	DFN 19 WW 120	8	E26	120	3 000	85	50 000	425	24	40	Y
61570	DFN 19 NW 120	8	E26	120	4 000	85	50 000	450	24	40	Y
61573	DFN 19 CW 120	8	E26	120	5 000	67	50 000	570	24	40	Y
G25											
61518	DFN 25 W27 120	8	E26	120	2 700	85	50 000	410	24	50	Y
61582	DFN 25 WW 120	8	E26	120	3 000	85	50 000	450	24	50	Y
61581	DFN 25 NW 120	8	E26	120	4 000	85	50 000	475	24	50	Y
61583	DFN 25 CW 120	8	E26	120	5 000	67	50 000	575	24	50	Y

NEW! DEFINITY™ A19

FEATURES

- Dimmable to 5 % of light on most dimmers.
- RoHS compliant – contains no mercury or lead.

MOL = 4 7/8 in. (111.5 mm)
Dia. = 2 3/8 in. (58 mm)



CERTIFICATIONS



ENVIRONMENT



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)	Dimmable (Yes/No)
GP19											
62272	DFN 19 40WE W27 120	6	E26	120	2 700	82	50 000	450	24	40	Y
62273	DFN 19 40WE WW 120	6	E26	120	3 000	82	50 000	450	24	40	Y
62274	DFN 19 40WE NW 120	6	E26	120	4 000	82	50 000	470	24	40	Y
62275	DFN 19 40WE CW 120	6	E26	120	5 000	82	50 000	480	24	40	Y

PRODUCT DESCRIPTION GUIDE

Family	Product	Wattage equivalency		Colour temperature		Voltage
DFN Definity	19 DFN19 19 A19 25 G25	40WE	40 Watt Equivalent	W27 WW NW CW	Warm White 2 700 K Warm White 3 000 K Neutral White 4 000 K Cool White 5 000 K	120 120 Volt 230 230 Volt ²

¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² 230 volts utilizes E27 base, otherwise consult factory.