



# Smart Interconnect Carbon Monoxide Alarm

Be sure to purchase a carbon monoxide alarm that has been approved under the new CSA 6.19-01 standard. This ensures both electrical and performance standards.



## Features:



- **120V AC Direct-Wire** – Interconnects with up to 24 units, of which 18 can be initiating.




- **Test / Reset Button** – Tests circuitry and resets alarm.
- Interconnectable – ANY unit that senses a problem automatically triggers ALL units throughout the home immediately, allowing extra time for escape.
- Smart Interconnect sounds a smoke alarm pattern when an interconnected Kidde smoke alarm detects fire or smoke.
- Originating alarm identifies which unit detected CO.

900-0132-05



CSA-6.19-01



## Specifications:

|                     |                                     |
|---------------------|-------------------------------------|
| Product dimensions: | 6" x 6" x 1.5" deep                 |
| Colour / Case Pack: | White / 6 units                     |
| Electrical Rating:  | 120V AC, 60Hz, 60mA max per alarm   |
| Wiring:             | Quick connect plug with 8" pigtails |
| Audio Alarm:        | 85dB                                |
| Temperature Range:  | 40°F (4.4°C) to 100°F (37.8°C)      |
| Humidity Range:     | 5% to 95% relative humidity         |
| Sensor:             | Electrochemical                     |
| Limited Warranty:   | 5 Year                              |
| Weight:             | 0.70lb                              |
| UPC:                | 0-55822-00132-2                     |

