




Representative



Line Art

**Catalog Number:** STX150-550  
**Product ID:** 7TBA051160R0018  
**UPC Number:** 78621090468  
**EAN Number:** 05415022460308  
**Status:** Active

Star Teck hazardous location aluminum jacketed cable fitting. Hub size of 1-1/2 inch. Range over jacket from 1.500 - 1.625 inch.

Working with engineers from the Canadian petrochemical, oil and gas industries, Thomas & Betts then introduced the STAR TECK XP fitting. With an easy-to-fill, integral sealing chamber and a disconnectable design requiring minimal cable preparation, this fitting became the benchmark for ease of installation in hazardous environments. A line of liquid and putty sealants was also developed at the same time, eliminating the need for the cement sealants used up to this point.

- Easy Fill and Assembly Sealing chamber is easier to fill, requires less sealing compound - saves time, material. Flame path is optimally designed to allow for easy insertion into hub. Quick-turn lock unitizes assembly during installation.
- Exclusive Power Grip Provides grip that/Es high upon cable armour - not on first convolution - so precise cable preparation is not critical. Non-magnetic stainless steel Power Grip grounding ring assures 360 degree long-term dependable grounding. Also provides phenomenal tensile pull out resistance.
- Easy to Install in Tight Spaces Low profile gland nut fits tightest spaces. Has grooves for hammer/ screwdriver installation and flats for wrench-gripping. Durable and reusable with funnel entry for easy cable insertion.
- Secure, Tight Fit Tapered bushing. Cone-shaped to provide secure, tight fit while eliminating cupping of water in vertical installations.

#### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	T&B Fittings
Type	Teck Cable Fittings
Application	For Hazardous Locations
Standard	UL E82038, CSA 23086
Size	1-1/2 inches
Material	Aluminum
Color	Silver and red

#### Packaging

Inner Quantity	1
Outer Quantity	4
Outer Dimensions (inches)	12.6x8.6x4.5
Weight Uom	148.44 lbs. per 100

#### Documents / Support Tools

Technical Drawing / Data Sheet	TDS000040
Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Catalogue Canada	Available on Website

#### Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120

ABB Installation Products Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289

