



Reflector PAR38 Krypton

K250PAR38/FL 120-130V 12PK

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These PAR Krypton flood lamps are available with medium skirted bases.

Product data


General Information	
Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]
Operating Position	Universal [Universal]
Gas Filling	KRYPTON
Nominal Lifetime (Nom)	4000 h
Switching Cycle	2 times per 24 h; minimum 15 minutes off
Light Technical	
Beam Angle (Nom)	30 °
Initial lumen (Nom)	3100 lm
Luminous Intensity (Max)	5000 cd
Beam Description	Flood [Flood]
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	250 W
Voltage (Nom)	120-130 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Eccentricity (Max)	1.0 mm
Skewness (Max)	2.5 mm
Product Data	
Order product name	Reflector 250W Med Skt 120-130V PAR38 FL 1CT
EAN/UPC - Product	046677374327
Order code	374322
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	923834636104
Net Weight (Piece)	307.000 g
ILCOS Code	IPAR-250-120/130-E26-121/30

Datasheet, 2018, July 23 data subject to change

Reflector PAR38 Krypton

Dimensional drawing



PAR38 250W E26/50x39 120-130V FL Kr

 Product
 D (max)
 C (max)
 C1

 Reflector 250W Med Skt 120-130V PAR38 FL 1CT
 122.5 mm
 135 mm
 121 mm



© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.