



Metal Clad Cable Termination Fittings & Accessories

T&B Catalog Number:

UPC Number: STX150-470
Status: 78621090469
Description: Active

Star Teck XP hazardous location aluminum jacketed cable fitting hub size 1-1/2 inches Range over jacket 1.350-1.625 inches.

Features

| | |
|--|--|
| | Sealing chamber is easier to fill, requires less sealing compound, saves time and material. |
| | Flame path is optimally designed to allow for easy insertion into hub, quick-turn lock. |
| | Union features twist-on action; red color for high visibility. |
| | Union features twist-on action; red color for high visibility. |
| | Exclusive power grip, provides grip that is high up on cable armor non-magnetic stainless steel power grip grounding ring. |
| | Low profile gland nut. |

Application

| | |
|--|---|
| | Provides means for passing armored, metal clad, jacketed cable through a bulkhead or enclosure in hazardous areas. (these fittings are suitable for hazardous areas when used with T&B sealing compound). |
| | Form a mechanical grip and water and/or oil-resistant termination. |
| | Provide grounding continuity of cable armor. |

General

| | |
|---|----------|
| Material | Aluminum |
| Sealing Compound Required-Putty (grams) | 80 |
| Sealing Compound Required-Liquid (cc) | 43 |

Dimension Information

| | |
|-------------------------------------|-------|
| Hub Size (inches) | 1 1/2 |
| Dimension A (inches) | 1.187 |
| Dimension B (inches) | 3.76 |
| Dimension C (inches) | 3.26 |
| Range Over Jacket -Minimum (inches) | 1.357 |
| Range Over Jacket -Maximum (inches) | 1.625 |
| Range Over Armor -Minimum (inches) | 1.240 |
| Range Over Armor -Maximum (inches) | 1.545 |

Specifications

| | |
|---------|----------------------|
| 3dmodel | Available on Website |
|---------|----------------------|

Packaging

| | |
|--------------------|---------------------|
| T&B Inner Pack | 1 |
| Package in Units | 4 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 145.94 lbs. per 100 |

Application Support

| | |
|-----------------------------------|----------------------|
| Product Specifications & Overview | Available on Website |
|-----------------------------------|----------------------|

Notes

| | |
|----------|------------------------------------|
| *Note | Class I, Div. 2, Groups A, B, C, D |
| **Note | Class II, Div. 2, Groups F, G |
| ***Note | Class III |
| ****Note | Enclosure Type 4 |

Certifications

| | |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

Certifications



File Nbr:
E 82038

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com