PHILIPS Lighting



Long Life IR PAR30S

Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1

Optically advanced Halogen PAR lamps are designed with innovative technologies that provide superior light performance while reducing operating costs.

Product data

General Information		
Base	E26 [Single Contact Medium Screw]	
Operating Position	Universal [Universal]	
Main Application	Accent & Downlighting	
Gas Filling	GAS	
Life with 3 Hour Per Day Use	3.8 a	
Light Technical		
Beam Angle (Nom)	40 °	
Initial lumen (Nom)	900 lm	
Luminous Intensity (Nom)	1550 cd	
Beam Description	Wide Flood [Wide Flood]	
Correlated Color Temperature (Nom)	2750 K	
Color Rendering Index (Nom)	100	
Operating and Electrical		
Power (Rated) (Nom)	50 W	
Voltage (Nom)	120 V	
Mechanical and Housing		
Bulb Finish	Clear (CL)	

Cap-Base Information	Brass [Brass Cap]		
Bulb Material	Hard Glass		
Reflector Finish	Aluminized		
Filament Shape	CC-8 [Axial]		
Approval and Application			
Estimated Energy Cost Per Year	6.02 \$		
Product Data			
Order product name	Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1		
EAN/UPC - Product	046677238001		
Order code	238006		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	15		
Material Nr. (12NC)	924757141301		
Net Weight (Piece)	210.000 g		

Long Life IR PAR30S

Dimensional drawing

Product	D	C (max)
Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1	3.75 in	4.5 in



PAR30 IRC 50W E26/BRC 120V WFL 40D CC-8



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2019, February 6 - data subject to change