



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Circuit Breakers](#) > [Molded Case Circuit Breakers](#)

Circuit Breakers,Molded Case Circuit Breakers

Product #: SELA36AI0030

Short Description: E-FRAME 3P 600V 30A MAG-BREAK

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Spectra RMS™ Electronic Trip
Product Line	Spectra RMS - Standard
Trip Style	Interchangeable
Frame Type	SE150
Amperage	15A , 20A , 25A , 30A
Poles	3
System Voltage	120 Vac , 120/240 Vac , 240 Vac , 277 Vac , 480 Vac , 600 Vac
120 Vac Interrupting Rating	100 KAIC
120/240 Vac Interrupting Rating	100 KAIC
240 Vac Interrupting Rating	100 KAIC
277 Vac Interrupting Rating	65 KAIC
480 Vac Interrupting Rating	65 KAIC
600 Vac Interrupting Rating	25 KAIC
Trip Function	Mag Only
Continuous Current Rated	Standard
Suitable for Reverse Feed	Yes
Lugs	TCAL18
Long Time	No
Instantaneous	Adjustable
Current Metering	No
Protective Relays	No
UL File #	E11592
CSA File#	LR40350
Height	12.0 in
GSA Compliance	No
GO Schedule	141S
UPC	078316422708
List Price	\$530



[View Larger](#)

Publications/Resources

[SELA36AI0030](#)

Additional Resources for Spectra RMS™ Electronic Trip

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[Time Current Curves](#)

[White Papers](#)

[BIM Files](#)

[Buy Log :3-73](#)

Spectra RMS Motor Circuit Protectors (SE150, SF250, SG600 and SK1200) have a digital, solid state, RMS sensing trip system with field installable, front-mounted rating plugs to establish or change the breaker ampere rating. Adjustable instantaneous with tracking short-time is standard on all frames. The trip system uses digital sampling to determine the RMS value of sinusoidal and non-sinusoidal currents.



ORLWDWIDE PARTNER