

TYPE WT TM

Features

- Manufactured from Nylon 66
- Available in UV Black
- Accepts .87" - 14.65" bundle diameter
- Tensile strength from 18 to 175 lbs.
- Permanently holds cable bundle without slippage
- One piece construction
- -40 to +185° F operating temperature range
- UL Listed, Type 21 rated
- Adhesive backed mounting bases – Type TM
- Cable tie mounts accommodate common mounting hardware
- Plenum rated AH-2

Benefits

- Resists chemicals
- Resists weather and ultraviolet light
- Versatility
- Strong and Flexible
- Self-Locking
- Precise shape for consistent performance and reliability
- Reliable in extreme temperature conditions
- Qualified positioning device
- Easy peel and stick installation
- For more stringent loading situations or difficult to adhere surfaces
- Application versatility




Fig. 1




Fig. 2




Fig. 3

Catalog Number	Figure Number	Color	Tensile Strength (lbs.)	Dimensions - in. (mm)				Max Bundle Diameter - in (mm)	
				L		W			
WT-040-018-N	1	Natural	18	3.937	(100.0)	0.098	(2.5)	0.866	(22.0)
WT-055-040-N	1	Natural	40	5.591	(142.0)	0.126	(3.2)	1.339	(34.0)
WT-075-050-N	1	Natural	50	7.480	(190.0)	0.189	(4.8)	1.929	(49.0)
WT-110-050-N	1	Natural	50	11.024	(280.0)	0.189	(4.8)	3.031	(77.0)
WT-145-050-N	1	Natural	50	14.488	(368.0)	0.189	(4.8)	4.134	(105.0)
WT-170-050-N	1	Natural	50	17.008	(432.0)	0.189	(4.8)	4.921	(125.0)
WT-240-175-N	1	Natural	175	24.016	(610.0)	0.354	(9.0)	6.969	(177.0)
WT-360-175-N	1	Natural	175	35.984	(914.0)	0.354	(9.0)	10.827	(275.0)
WT-480-175-N	1	Natural	175	47.992	(1219.0)	0.354	(9.0)	14.646	(372.0)
WT-040-018-B	1	UV Black	18	3.937	(100.0)	0.098	(2.5)	0.866	(22.0)
WT-055-040-B	1	UV Black	40	5.591	(142.0)	0.126	(3.2)	1.339	(34.0)
WT-075-050-B	1	UV Black	50	7.480	(190.0)	0.189	(4.8)	1.929	(49.0)
WT-110-050-B	1	UV Black	50	11.024	(280.0)	0.189	(4.8)	3.031	(77.0)
WT-145-050-B	1	UV Black	50	14.488	(368.0)	0.189	(4.8)	4.134	(105.0)
WT-170-050-B	1	UV Black	50	17.008	(432.0)	0.189	(4.8)	4.921	(125.0)
WT-240-175-B	1	UV Black	175	24.016	(610.0)	0.354	(9.0)	6.969	(177.0)
WT-360-175-B	1	UV Black	175	35.984	(914.0)	0.354	(9.0)	10.827	(275.0)
WT-480-175-B	1	UV Black	175	47.992	(1219.0)	0.354	(9.0)	14.646	(372.0)

Catalog Number	Figure Number	Color	Dimensions - in. (mm)						Mounting Hole
			L		W		H		
TM-075-N†	2	Natural	0.768	(19.5)	0.768	(19.5)	0.154	(3.9)	0.126 (3.2)
TM-100-N†	3	Natural	1.028	(26.1)	1.028	(26.1)	0.236	(6.0)	0.177 (4.5)

Flammability rating UL94V-2; cable ties and mounts

† Not plenum rated