

Round floor boxes for power or communications

600 Series



Features – 600 Series

- Cast iron, watertight body, fully adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- Interior and exterior leveling screws permit adjustment to meet finished floor
- Shipped complete with expendable cap to prevent ingress of concrete during pour
- 3/4" threaded conduit openings are standard
- Uses P60 Series MopTite* covers and carpet plate, see page 23













at. No.	Description	Std. Ctn.
00-SC	Cast-iron floor box 3/4" conduit tapping	4
00-AL-SC	Cast-iron floor box 3/4" conduit tapping with aluminum trim ring	4
00-1-SC	Cast-iron floor box 1" conduit tapping	4
00 1 1/4AL	Cast-iron floor box 11/4" conduit tapping	4
00-2-SC	Cast-iron floor box 2" conduit tapping	4
01-1/2-SC	Cast-iron floor box 1/2" conduit tapping	4
01-AL-SC	Cast-iron floor box 3/4" conduit tapping with aluminum trim ring	4
01-SC	Cast-iron floor box 3/4" conduit tapping	4
01-1	Cast-iron floor box 1" conduit tapping	4
01-1-1/4	Cast-iron floor box 1½" conduit tapping	4
02-SC	Cast-iron floor box 3/4" conduit tapping	4
02-AL-SC	Cast-iron floor box 3/4" conduit tapping with aluminum trim ring	4
02-1	Cast-iron floor box 1" conduit tapping	4
03-SC	Cast-iron floor box 3/4" conduit tapping	4
03-AL-SC	Cast-iron floor box 3/4" conduit tapping with aluminum trim ring	4
04-SC	Cast-iron floor box 3/4" conduit tapping	4
04-AL-SC	Cast-iron floor box 3/4" conduit tapping with aluminum trim ring	4
00-4-FL	Trim ring brass	4
00-4-FL-AL	Trim ring aluminum	4

P-60 Covers sold separately.

Round floor boxes for power or communications

600 Series



Features - 600 Series

- Cast iron, watertight body, fully adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- Interior and exterior leveling screws permit adjustment to meet finished floor
- Shipped complete with expendable cap to prevent ingress of concrete during pour
- ¾" threaded conduit openings are standard
- Uses P60 Series MopTite* covers and carpet plate, see page 23


Engineering data






		Dimens	ions (in.)	Before	. pour adj.	Maximum		Condu	it KOs (in.)
Cat. No.	A	В	С	pour adj. (in.)		capacity kos (cu. in.)	Conduit hubs	Sides	Bottom
600-SC	41/4	41/4	51/8	21/2	¹⁵ / ₁₆	64	3/4	_	_
600-1-SC	41/4	41/4	51/8	21/2	¹⁵ / ₁₆	64	1	_	_
600-11/4AL	41/4	41/4	51/8	21/2	¹⁵ / ₁₆	64	11/4	_	_
600-2-SC	41/4	41/4	51/8	21/2	¹⁵ / ₁₆	64	2	_	_
601-SC	41/4	39/16	51/8	21/2	¹⁵ / ₁₆	56	3/4	_	_
601-1	41/4	39/16	51/8	21/2	¹⁵ / ₁₆	56	1	_	_
601-11/4	41/4	31/16	51/8	21/2	¹⁵ / ₁₆	56	11/4	_	_
602-SC	41/4	31/32	4	21/2	¹⁵ / ₁₆	36	3/4	_	_
602-1	41/4	31/32	4	21/2	¹⁵ / ₁₆	36	3/4	_	_
603-SC	41/4	21/2	4	21/2	11/16	27	3/4	_	_
604-SC	41/4	2	4	1 ¹ / ₂	_	15	3/4	_	_

Use P-60 Series covers and carpet plates. Wiring Device: Duplex, single or voice/data plates.





MopTite® carpet plates

600 Series

01 P-60-3/4-2-CACP

- Polished brass finish
- Integrated carpet plate and ³/₄"-2" floor plate in one unit
- Furnished complete with sealing gasket and 8-32 x 1" brass screws
- 5³/₄" outside diameter

02 P-60-CP

- Polished brass finish
- Furnished complete with 8-32 x 1" brass screws
- For brushed aluminum, add AL after catalog number

03 P-60-LCP

- Translucent polycarbonate
- Textured finish

04 P-60-CACP

- Polished-brass finish
- Integrated carpet plate and duplex floor plate in one unit

05 P-60-CACP-GFCI

- Furnished complete with sealing gasket and 8-32 x 1" brass
 screws
- screws
 5³/₄" outside diameter


















Cat. No.	Description	Std. Ctn.
P-60-CP	Brass carpet plate, 511/16" diameter	4
P-60-CPAL	Aluminum carpet plate	4
P-60-LCP	Polycarbonate carpet plate, 53/8" diameter	4
P-60-CACP	Brass one-piece carpet cover plate	4
P-60-CACP-AL	Aluminum one-piece carpet plate	4
P-60-3/4-2-CACP	Brass one-piece carpet plate with 3/4"-2" plugs	4
P60-3/4-2-CACP-AL	Aluminum one-piece carpet plate with 3/4"-2" plugs	4
P60-CACP-GFCI	Brass one-piece carpet plate for GFCI devices	4
P60-CACP-GFCI-AL	Aluminum one-piece carpet plate for GFCI devices	4

 ${\tt MopTite} @\ Covers\ exceed\ {\tt UL/CSA}\ scrubwater\ exclusion\ requirements.$



MopTite® cover plates

600 Series

Features and benefits:

- · Polished finish
- Furnished complete with sealing gasket and 8-32 x $^{7}/_{16}{}^{\shortparallel}$ screws
- 4" outside diameter



P-60-1/2 ½" N.P.S. plug size



P-60-2* 2" dia. plug size



P-60-DR* Duplex liftlid



P-60-3/4 3/4" N.P.S. plug size



P-60-2-5/8* 2⁵/₈" dia. plug size



P-60-DU* Duplex ¹⁷/₁₆" plugs




P-60-1 1" N.P.S. plug size



P-60-1/2-2*
½" & 2" dia. plug size



P-60-DS* Hinged liftlids



P-60-1-1/4




P-60-3/4-2*
3/4" & 2" dia. plug size



P-60-GFCI*







Cat. No.	Description	Std. Ctn.
P-60-1/2	Brass cover plate ½" NPS plug size	4
P-60-1/2-AL	Aluminum cover plate ½" NPS plug size	4
P-60-3/4	Brass cover plate 3/4" NPS plug size	4
P-60-3/4-AL	Aluminum cover plate 3/4" NPS plug size	4
P-60-1	Brass cover plate 1" NPS plug size	4
P-60-1-AL	Aluminum cover plate 1" NPS plug size	4
P-60-1-1/4	Brass cover plate 11/4" NPS plug size	4
P-60-1-1/4-AL	Aluminum cover plate 11/4" NPS plug size	4
P-60-2	Brass cover plate 2" diameter plug size	4
P-60-2-AL	Aluminum cover plate 2" diameter plug size	4
P-60-2-5/8	Brass cover plate 25/8" diameter plug size	4
P-60-2-5/8-AL	Aluminum cover plate 25/8" diameter plug size	4
P-60-1/2-2	Brass cover plate ½"–2" diameter plug size	4
P-60-1/2-2-AL	Aluminum cover plate ½"-2" diameter plug size	4
P-60-3/4-2	Brass cover plate ³ / ₄ "–2" diameter plug size	4
P-60-3/4-2-AL	Aluminum cover plate 3/4"-2" diameter plug size	4
P-60-DR	Brass cover with duplex lift lid	4
P-60-DS	Brass cover for duplex with individual lift lids	4
P-60-DS-AL	Aluminum cover for duplex with individual lift lids	4
P-60-DU	Brass cover plate with two 11/16" plugs for duplex	4
P-60-DU-AL	Aluminum cover with two 1% 6" plugs for duplex	4
P-60-GFCI	Brass cover plate for GFCI devices	4
P-60-GFCI-AL	Aluminum cover plate for GFCI devices	4


Floor boxes for single short-strap receptacles or communications

78 Series

Service fitting application

78 Series Floor boxes provide flush service for power or communications and data. They can be used for either carpet or tile applications.





78 Series – features and benefits:

- · Cast iron, watertight body, semi-adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- Exterior leveling screws and threaded vertical adjusting ring permit adjustment to meet finish floor
- Shipped complete with expandable cap to prevent ingress of concrete during pour
- 3/4" threaded conduit openings
- Uses P90 Series MopTite® covers





Cat. No.	Description	Std. Ctn.
78SC	Cast-iron single-gang floor box with 3/4" conduit tapping	4
78-S	Cast-iron single-gang floor box (shallow)	4

Engineering Data





		Dimensio	ons (in.)	Before pour adj.	After pour adj.	Maximum capacity	Standard conduit tapping	
Cat. No.	Α	В	С	(in.)	(in.)	(cu. in.)	(in.)	
78SC	3	213/16	37/8	21/2	3/4	24	3/4	
78-S	3	25/8	37/8	11/2	3/4	20	3/4	

	Maximum con	duit tapping (in.)	Coi	nduit KOs (in.)	Covers and	Wiring device	
Cat. No.	w/bushing	w/o bushing	Sides	Bottom	Carpet Plates		
78SC	3/4	1	_	_	P90 series	Sing. short, strap rec.	
78-S	3/4	1	_	_	P90 series	Sing. short, strap rec.	

MopTite® cover plates

78 Series





P-90-3/4-AL 3/4" N.P.S. plug

P-90-1-AL 1" N.P.S. plug





P-90-1-1/4 11/4" N.P.S. plug

P-90-2-AL* 2" dia. plug










P-90-3/4-2* 3/4" & 2" dia. plugs



Features and benefits:

- · Polished-brass finish
- Furnished complete with sealing gasket and 6-32 x 1/2" screws
- 213/16" outside diameter





Cat. No.	Description	Finish	Std. Ctn.
P-90-3/4-AL	Cover plate 3/4" NPS plug	Aluminum	4
P-90-1-AL	Cover plate 1" NPS plug	Aluminum	4

MopTite® Covers exceed UL/CSA watertight requirements.

		•	Std.
Cat. No.	Description	Finish	Ctn.
P-90-1-1/4-AL	Cover plate 1 ¹ / ₄ " NPS plug	Aluminum	4
P-90-2-AL	Cover plate 2" UN plug	Aluminum	4
P-90-1/2-2	Cover plate 1/2" & 2" plug	Brass	4
P-90-3/4-2	Cover plate 3/4" & 2" plug	Brass	4
P-90-3/4-2-AL	Cover plate 3/4" & 2" plug	Aluminum	4

Accessories

78 Series

- 15-Amp, 125-Volt, NEMA grounding type
- Mounted on steel seating plate
- For use with 2" diameter-opening floor plate

Carpet plate

78 Series

- · Polished-brass finish
- Furnished complete with 6-32 x 1" brass flathead screws and gasket
- Threaded 2-20UN-2B to accept 694 plug
- 3%" O.D. with %" flange



478-G-12



Cat. No.	Description	Std. Ctn.
478-G-12	15-Amp 125-Volt NEMA grounding receptacle	4







Cat. No.	Description	Finish	Std. Ctn.
P-90-CP	Carpet plate	Brass	4

^{*}Also includes steel seating plates for receptacles.

Floor boxes for single short-strap receptacles or communications

671 and 672 Series

671 and 672 Series floor boxes provide flush service for power or communications and data.


They can be used in either wood or concrete floors and are suitable for carpet, tile or wood applications.


Features and benefits:

- · Cast iron, watertight, non-adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- · For use in wood or concrete floors
- ½" and ¾" threaded conduit openings; uses P67 Series covers
- · Cat. No. 672 is the 671 floor box with factorymounted 15-ampere, 125-volt, NEMA grounding receptacle and P67-2 MopTite® cover plate













	Dimensions (in.)			Maximum capacity	Standard conduit	Maximum conduit tapping (in.)		Conduit KOs (in.)			Covers/ KOs (in.) carpet		Covers/ Conduit KOs (in.) carpet			Std.
Cat. No.	Α	В	С	(cu. in.)	tapping	w/bushing	w/o bushing	Sides	Bottom	Sides	Bottom	plates	Wiring Device	Ctn		
671SC	31/2	3	231/32	13	(2)-3/4"	3/4	3/4	(2) ¹ / ₂	(2) ½	(2) 3/4	_	P67 Series	Sing. short strap rec	4		
672	3 ¹ / ₂	33/16	2 ³¹ / ₃₂	13	(4)- ¹ / ₂ "	3/4	3/4	(2) ¹ / ₂	(2) ¹ / ₂	(2) ³ / ₄	_	P67 Series	Sing. short strap rec	4		

MopTite® Covers exceed UL/CSA watertight requirements.

MopTite® Plates

671 and 672 Series



P-67-1/2 1/2" N.P.S. plug



P-67-1 1" N.P.S. plug







*Also includes seating plate for receptacle.



P-67-3/4

3/4" N.P.S. plug

P-67-1-1/4*


11/4" N.P.S. plug




P-67-3/4-2* 3/4" & 2" dia. plugs


- - · Furnished complete with sealing gasket and 6-32 x 1/2" screws
 - 3½" outside diameter

· Polished brass finish





Cat. No.	Description	Finish	Std. Ctn.
P-67-1-1/4	Cover plate with 1 ¹ / ₄ " NPS plug	Brass	4
P-67-2	Cover plate with 2" UN thread plug	Brass	4
P-67-2-AL	Cover plate with 2" UN thread plug	Aluminum	4
P-67-1/2-2	Cover plate with ½" & 2" plug	Brass	4
P-67-3/4-2	Cover plate with 3/4" & 2" plug	Brass	4





Carpet plates

671 and 672 Series



Features and benefits:

- Polished-brass finish
- Furnished complete with 6-32 x 1"-long brass flathead screws and gasket
- 33/8" outside diameter



Cat. No.	Description	Std. Ctn.
P-90-CP	Carpet plate – Brass	4

Will not accept P-67 covers, will accept threaded plug, see page 127.

Accessories

671 and 672 Series







478-G-12 Short strap receptacle

Features and benefits:

- Use brass edge ring for neat appearance when non-adjustable floor box is installed in concrete
- Edge ring has $3\frac{3}{4}$ " OD and adds $\frac{3}{6}$ " to floor box height
- 15-amp, 125-volt, NEMA grounding type
- Mounted on steel seating plate
- For use with 2" diameter opening floor plate





Cat. No.	Description	Std. Ctn.
P-67-F	Brass edge ring for concrete	4
478-G-12	15-Amp, 125-Volt NEMA grounding receptacle	4

Multiple-gang floor boxes for power and communications

640 and 840SC Series

640 and 840 Series floor boxes provide flush service for power, communications and data. Multiple-gang boxes enable the user to place high- and low-voltage in a single floor box.

Floor boxes up to four-gangs are available. 640 and 840 Series boxes can be used for either carpet or tile applications.


640 Series - features and benefits:

- · Cast iron, watertight body, fully adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- Interior and exterior leveling screws permit adjustment to finished floor
- Removable partitions for large capacity requirements on 2-, 3- and 4-gang
- Shipped complete with expendable cap to prevent ingress of concrete during pour
- 3/4" threaded conduit openings are standard
- Uses P64 Series MopTite® covers (one cover per gang)

840SC Series - features and benefits

- · Cast iron, watertight body, semi-adjustable
- Painted silver enamel inside and out for additional corrosion resistance
- Exterior leveling screws for adjustment to finished floor
- Removable partitions for large capacity requirements on 2- and 3-gang
- Shipped complete with expendable cap to prevent ingress of concrete during pour
- ¾" threaded conduit openings are standard
- Uses P64 Series MopTite® covers (one cover per gang)







Features and benefits:

- · Polished brass finish
- Furnished complete with sealing gasket and 8-32 x 1" screws
- 3" x 4½" outside dimension
- All covers meet MopTite® requirements

Multiple-gang floor boxes for power and communications


640 and 840SC Series





Engineering data






Cat. No.	Number of gangs	Maximum capacity (cu. in.)	Conduit hubs (in.)
641	1	35	3/4
642	2	37 per gang	3/4
643	3	37 per gang	3/4
841-SC	1	15	3/4
842-SC	2	16.5 per gang	3/4
843-SC	3	16.5 per gang	3/4


Use P64 Series covers and carpet plates.


Floor boxes

640 and 840SC Series










^{*}Additional hub sizes available — see next page.

MopTite® cover plates

640 and 840 Series





P-64-3/4

3/4" N.P.S. plug





1¼" N.P.S. plug

P-64-1-1/4







P-64-GFCI

P-64-1/2 ½" N.P.S. plug

P-64-2* 2" dia. plug





P-64-1

1" N.P.S. plug



Cat. No.	Description	Finish	Std. Ctn.
P-64-1/2	Cover plate ½" NPS plug	Brass	4
P-64-3/4	Cover plate 3/4" NPS plug	Brass	4
P-64-3/4-AL	Cover plate 3/4" NPS plug	Aluminum	4
P-64-1	Cover plate 1" NPS plug	Brass	4
P-64-1-AL	Cover plate 1" NPS plug	Aluminum	4
P-64-1-1/4	Cover plate 11/4" NPS plug	Brass	4
P-64-1-1/4-AL	Cover plate 1 ¹ / ₄ " NPS plug	Aluminum	4
P-64-2	Cover plate 2" UN plug	Brass	4
P-64-2-AL	Cover plate 2" UN plug	Aluminum	4
P-64-1/2-2	Cover plate ½" & 2" UN plug	Brass	4

MopTite® Covers exceed UL/CSA scrubwater exclusion requirements. For replacement plug see page 127.

Cat. No.	Description	Finish	Std. Ctn.
P-64-1/2-2-AL	Cover plate ½" & 2" UN plug	Aluminum	4
P-64-3/4-2	Cover plate 1/4" & 2" UN plug	Brass	4
P-64-3/4-2-AL	Cover plate 3/4" & 2" UN plug	Aluminum	4
P-64-DS	Cover plate duplex Lift lids	Brass	4
P-64-DS-AL	Cover plate duplex Lift lids	Aluminum	4
P-64-2-5/8	Cover plate 25/8" UN plug	Brass	4
P-64-2-5/8-AL	Cover plate 25/8" UN plug	Aluminum	4
P-64-DU	Cover plate duplex 11/16" plugs	Brass	4
P-64-DU-AL	Cover plate duplex 1½6" plugs	Aluminum	4
P-64-GFCI	Cover plate GFCI flip lid	Brass)	4
P-64-GFCI-AL	Cover plate GFCI flip lid	Aluminum	4

Metallic carpet plates

640 and 840 Series









Cat. No.	Number of gangs	Outside Dimension (in.)	Material	Std. Ctn.
P64-CP	1	45/8 x 61/8	Brass	4
P64-CP-AL	1	4 ⁵ / ₈ x 6 ¹ / ₈	Aluminum	4
P64-2G-CP	2	7 ⁵ /8 x 6 ¹ /8	Brass	4
P64-2G-CP-AL	2	7 ⁵ /8 x 6 ¹ /8	Aluminum	4
P64-3G-CP	3	105/8 x 61/8	Brass	4
P64-3G-CP-AL	3	105/8 x 61/8	Aluminum	4

Gaskets

Floor plate assemblies







Cat. No.	For use with	Std. Ctn.
SP650	P-64 Series floor plate assemblies	4
SP651	P-64-DU floor plate assemblies	10
SP-P64-DS-P2	P-64-DS floor plate assembly	4