




UPC Code : 07847743408

Country Of Origin : China



Available Colors :



M58AC-HGI

Tamper-Resistant USB Receptacle, Type A/C, 20 Amp 125 Volt, Hospital Grade, Ivory - Lev-Lok

Lev-Lok Combination Tamper-Resistant Duplex Decora Receptacle and Dual-Port USB Type A-C Charger, NEMA 5-20R, 20A-125V, 2 Pole, 3-Wire Grounding Receptacle – Ivory

Lev-Lok employs a simple twist and lock wiring module to provide a safe and secure connection. These devices are pre-wired for 3x faster installations and 5x faster swap outs than traditional wiring. The speed and ease of Lev-Lok allows for optimal time, labor, and cost savings.

The M58AC:

- One Type A and one Type C USB port with a combined total of 5.1A of charging power, the fastest in the industry
- Type A USBs are the most recognized and commonly used USB port, used in most desktops, laptops, and tablets, while Type C USBs are emerging as the latest standard for charging and transferring data
- Common applications: health care facilities, lobbies & waiting rooms, airports, hospitality, and educational institutions
- For use with MSTWL Lev-Lok wiring modules only, modules sold separately

Technical Information

Electrical Specifications

Amperage : 20 A

Current Interrupting : Certified for full-rated current and voltage

Dielectric Voltage : 2000 VAC

Grounding : Self-Grounding

Horsepower Rating : 1 hp

Pole : 2

Temperature Rise : Max 30°C

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : Maximum Continuous 40°C, Minimum -10°C (w/o impact)

Material Specifications

Body Material : PBT

Face Material : Thermoplastic

Ground Clips : Brass

Ground Contacts : Brass

Locking Pins : Solid Brass

Mounting Screws : #6 Plated Steel

Mounting Strap : Galvanized Steel

Shutter Material : Thermoplastic

Shutter Mechanism : Acetal

Mechanical Specifications

Product ID : Ratings are marked on device

Strap Construction : Through-Strap

Termination : Modular

Product Features

Brand : Lev-Lok

Color : Ivory

Device Type : Combination Device

Feature : USB Type A and USB Type C, Tamper-Resistant

Grade : Heavy-Duty Hospital Grade

NEMA : 5-20R

USB Specifications

Single Port Charging Power : 15W

Total Charging Power : 25W

USB Cable Compatible : Type A and Type C

USB Charger : 5.1A

Standards & Certifications

Applicable Standards : UL 498, CSA C22.2, No. 42, UL 1310, UL 94, NOM, FCC Class B

NEMA : WD-1 and WD-6

Warranty

Warranty : 5-Year Limited

Patents*

CA2621644	US7357652
CA2624409	US7666010
CA2655707	US7820909
CA2667092	US7868719
CA2677283	US8096818
CN200880004760.2	US8242362
MX338817	US9368982
US7355117	US9496726

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

