



T&B®

Metal Clad Cable Termination Fittings & Accessories

T&B Catalog Number:

STX350-480

UPC Number:

78621090459

Status:

Active

Description:

Star Teck XP hazardous location aluminum jacketed cable fitting hub size 3-1/2 inches Range over jacket 3.00-3.27 inches.

Features

	Sealing chamber is easier to fill, requires less sealing compound, saves time and material.
	Flame path is optimally designed to allow for easy insertion into hub, quick-turn lock.
	Union features twist-on action; red color for high visibility.
	Union features twist-on action; red color for high visibility.
	Exclusive power grip, provides grip that is high up on cable armor non-magnetic stainless steel power grip grounding ring.
	Low profile gland nut.

Application

	Provides means for passing armored, metal clad, jacketed cable through a bulkhead or enclosure in hazardous areas. (these fittings are suitable for hazardous areas when used with T&B sealing compound).
	Form a mechanical grip and water and/or oil-resistant termination.
	Provide grounding continuity of cable armor.

General

Material	Aluminum
Sealing Compound Required-Putty (grams)	965
Sealing Compound Required-Liquid (cc)	464

Dimension Information

Hub Size (inches)	3 1/2
Dimension A (inches)	2.864
Dimension B (inches)	6.32
Dimension C (inches)	5.79
Range Over Jacket -Minimum (inches)	3.000
Range Over Jacket -Maximum (inches)	3.270
Range Over Armor -Minimum (inches)	2.880
Range Over Armor -Maximum (inches)	3.190

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	6.4 lbs. Each

Application Support

Product Specifications & Overview	Available on Website
-----------------------------------	----------------------

Notes

*Note	Class I, Div. 2, Groups B, C, D
**Note	Class II, Div. 2, Groups F, G
***Note	Class III
****Note	Enclosure Type 4

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications

File Nbr:
E 82038

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com