

550-650 W High Wattage Fan Heater scr Series





Features

- For large heating capacity requirements.
- Maintains minimum operating temperatures in enclosures.
- Helps prevent failures to components caused by condensation and corrosion.
- Built-in thermostat and control light.
- Heating power adjusts to ambient temperature.
- Heat exits top of fan heater. (add 2" clearance for heat sensitive parts)

| | | Inrush | | Temperature | Ship Wt. |
|--------------|-------|----------------|--------|------------------|----------|
| Part No. | Watts | Current (Amps) | Volts | Maximum with Fan | lbs |
| SCR027009 | 550 W | 11 A | AC 120 | 250°F/120°C | 2 |
| SCR027009230 | 550 W | 13 A | AC 230 | 250°F/120°C | 2 |
| SCR027019 | 650 W | 12 A | AC 120 | 320°F/160°C | 2.4 |

| Air Flow: | 20 CFM (550W), 26 CFM (650W) | | |
|-------------------|---|--|--|
| Thermostat Range: | 32 - 140 degrees Fahrenheit | | |
| Heating Element: | PTC - Semiconductor/resistor | | |
| Housing: | Plastic, rated UL94-VO | | |
| Connection: | 3 pole terminal, AWG 14 max (2.5 mm2) | | |
| Mounting: | Clip for 35mm DIN rail | | |
| Protection Class: | II (Double Insulated) | | |
| Protection Type: | IP20 | | |
| Approval: | UL Recognized Component, cUL Recognized Component, CE | | |

Data subject to change without notice