

Pulse Start

Applications

- Parking garage
- Security lighting
- Big box retail
- Residential roadways
- Warehouse lighting
- Lowbay industrial lighting
- Site lighting



PulseStart™



O = Open rated for indoor fixtures E = Enclosed rated

Order code	Description	Shape	Base	ANSI code	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Mean lumens (lm)	Burn pos.	Finish	Luminaire	Case qty	Figure
250 watts														
58072	MS250W/V/PS/740 STD	ED28	E39	M153/E	4 000	65	20 000	25 000	19 000	BU±15°	Clear	E	12	E
57999	MS250W/C/V/PS/737 STD	ED28	E39	M153/E	3 700	70	20 000	23 800	18 088	BU±15°	Coated	E	12	F
57998	MS250W/H75/PS/740 STD	ED28	E39	M153/E	4 000	68	10 000	22 000	17 600	HOR±75°	Clear	E	12	E
57980	MP250W/BU/UVS/PS/740 STD	ED28	EX39	M153/O	4 000	65	15 000	23 800	19 000	BU±15°	Clear	O	12	H
58059	MP250W/C/BU/UVS/PS/737 STD	ED28	EX39	M153/O	3 700	70	15 000	22 600	18 080	BU±15°	Coated	O	12	G
320 watts														
57964	MS320W/V/ED37/PS/740 STD	ED37	E39	M154/E	4 000	65	20 000	33 000	26 400	BU±15°	Clear	E	6	I
57996	MS320W/H75/T15/L/PS/740 STD	T15	E39	M154/E	4 000	68	20 000	30 000	24 000	HOR±75°	Clear	E	12	M
57973	MS320W/V/ED28/PS/740 STD	ED28	E39	M154/E	4 000	65	20 000	33 000	26 400	BU±15°	Clear	E	12	E
59147	MS320W/H75/ED28/PS/740 STD	ED28	E39	M154/E	4 000	68	10 000	30 000	24 000	HOR±75°	Clear	E	12	E
58026	MP320W/BU/ED28/UVS/PS/740 STD	ED28	EX39	M154/O	4 000	65	20 000	31 000	24 800	BU±15°	Clear	O	12	H
58027	MP320W/C/BU/ED28/UVS/PS/737 STD	ED28	EX39	M154/O	3 700	70	20 000	29 000	23 200	BU±15°	Coated	O	12	G
58051	MP320W/BU/ED37/UVS/PS/740 STD	ED37	EX39	M154/O	4 000	65	20 000	31 000	24 800	BU±15°	Clear	O	6	L
58060	MP320W/C/BU/ED37/UVS/PS/737 STD	ED37	EX39	M154/O	3 700	70	20 000	29 000	23 200	BU±15°	Coated	O	6	J
350 watts														
59148	MS350W/V/ED28/PS/740 STD	ED28	E39	M131/E	4 000	68	20 000	37 000	29 000	BUD±15°	Clear	E	12	E
58071	MS350W/H75/ED28/PS/740 STD	ED28	E39	M131/E	4 000	68	26 000	33 000	26 000	HOR±75°	Clear	E	12	E
58024	MS350W/V/PS/740 STD	ED37	E39	M131/E	4 000	65	20 000	37 000	29 000	BU±15°	Clear	E	6	I
57988	MS350W/C/V/PS/737 STD	ED37	E39	M131/E	3 700	70	20 000	35 000	28 000	BU±15°	Coated	E	6	K
58052	MP350W/V/UVS/PS/740 STD	ED37	EX39	M131/O	4 000	65	20 000	35 000	28 000	BU±15°	Clear	O	6	L
59146	MP350W/C/V/UVS/PS/737 STD	ED37	EX39	M131/O	3 700	70	20 000	33 000	26 000	BU±15°	Coated	O	6	J