



# T&B®

## Metal Clad Cable Termination Fittings & Accessories

**T&B Catalog Number:**

STX200-474

**UPC Number:**

78621090464

**Status:**

Active

**Description:**

Star Teck XP hazardous location aluminum jacketed cable fitting hub size 2 inches Range over jacket 2.100-2.375 inches.

### Features

	Sealing chamber is easier to fill, requires less sealing compound, saves time and material.
	Flame path is optimally designed to allow for easy insertion into hub, quick-turn lock.
	Union features twist-on action; red color for high visibility.
	Union features twist-on action; red color for high visibility.
	Exclusive power grip, provides grip that is high up on cable armor non-magnetic stainless steel power grip grounding ring.
	Low profile gland nut.

### Application

	Provides means for passing armored, metal clad, jacketed cable through a bulkhead or enclosure in hazardous areas. (these fittings are suitable for hazardous areas when used with T&B sealing compound).
	Form a mechanical grip and water and/or oil-resistant termination.
	Provide grounding continuity of cable armor.

### General

Material	Aluminum
Sealing Compound Required-Putty (grams)	150
Sealing Compound Required-Liquid (cc)	80

### Dimension Information

Hub Size (inches)	2
Dimension A (inches)	1.995
Dimension B (inches)	4.15
Dimension C (inches)	4.02
Range Over Jacket -Minimum (inches)	2.100
Range Over Jacket -Maximum (inches)	2.375
Range Over Armor -Minimum (inches)	1.990
Range Over Armor -Maximum (inches)	2.280

### Specifications

3dmodel	Available on Website
---------	----------------------

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	2.21 lbs. Each

**Application Support**

Product Specifications & Overview	Available on Website
-----------------------------------	----------------------

**Notes**

*Note	Class I, Div. 2, Groups A, B, C, D
**Note	Class II, Div. 2, Groups F, G
***Note	Class III
****Note	Enclosure Type 4

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**Certifications**

File Nbr:  
E 82038

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)