

LM150



Brand Features

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status at-a-glance.

**For applications up to 60A when using copper wire; or 50A when using aluminum wire*

Item Description

Main Circuit Breaker, 2-Pole, 150 Amp, 120/240 VAC, 22KA Interrupt Rating

Technical Information

Electrical Specifications

Amperage: 150 A

Operating Temperature: -40°C to 85°C

Pole: 2 Poles

Short Circuit Current Rating: 22 KA

Type: Main

Voltage: 120/240 VAC

Mechanical Specifications

Weight: 2.83 lbs.

Wiring: 6 AWG - 300 MCM Cu/Al

Standards & Certifications

CSA-C22.2 No. 5-02: Yes

EMC Compatibility: Yes

FCC: Yes

RoHS: Yes

UL 489: Molded Case Circuit Breakers

UPC Code: 07847781608

Country Of Origin: Mexico

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

