



S4			S5			S6			S6			S7	S8
250			400			600			800			1200	1600/2000/2500
600			600			600			600			600	600
3000			3000			3000			3000			3000	3000
8			8			8			8			8	8
2/3/4			2/3/4			2/3/4			2/3/4			2/3/4	3
N	H	L	N	H	L	N	H	L	N	H	L	H	V
65	150	200	65	150	200	65	150	200	65	150	200	100	120
25	65	100	35	65	100	50	65	100	50	65	100	65	100
18	22	35	22	22	35	25	35	42	25	35	42	50	85
—	—	—	35	50	65	35	50	65	35	50	65	—	—
—	—	—	20	35	50	20	35	50	20	35	50	—	—
65	100	200	65	100	200	65	100	200	65	100	200	100	120
35	65	100	35	65	100	35	65	100	35	65	100	65	120
30	50	80	30	50	80	30	50	80	30	50	80	55	100
25	40	65	25	40	65	25	40	65	25	40	65	45	70
18	22	30	20	25	30	20	25	35	20	25	35	25	50
—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—
10.0 x 4.13 x 4.07 10.0 x 5.51 x 4.07			10.00 x 5.51 x 4.07 10.00 x 7.24 x 4.07			10.55 x 8.27 x 4.07 10.55 x 11.0 x 4.07			14.25 x 8.27 x 4.07 14.25 x 11.0 x 4.07			15.98 x 8.27 x 5.45 15.98 x 11.0 x 5.45	15.75 x 15.98 x 9.25 —
25,000			20,000			20,000			20,000			10,000	10,000
120			120			120			120			120	20
8.8			11.0			21.0			22.0			37.5	135

Standard cable lug kits			
For breakers	Amps	Wire range	Catalog number
S3	60	14AWG - 2AWG	K3TA
S3 - S4	100	14AWG - 1/0	K4TB
S3 - S4	150	2AWG - 4/0	K4TC
S3 - S4 - S5	225	4awg - 300kcmil	K4TD
S4	250	6AWG - 350kcmil	K4TE
S5	300	250kcmil - 500kcmil	K5TF
S5	400	(2) 3/0 - 250kcmil	K5TG
S6	600	(2) 250kcmil - 500kcmil	K5TH
S6	800	(3) 2/0 - 400kcmil	K6TJ
S7	1200	(4) 4/0 - 500kcmil	K7TK
S8	1600	(4) 1/0 - 750kcmil	K8TL
S8	2500	(6) 1/0 - 750kcmil	K8TM

Standard cable lugs, for use on load side of circuit breaker. Suitable for use with Cu or Al. Special versions available with taps and screw for control wire connection.
 Note: S6 and S7 lugs are Al9Cu (90°); all others AL7Cu (75°C). Must use wire based on 75°C ampacity.

K4TB

