



UPC Code: 07847781474 Country Of Origin: Mexico

LB120-EP

Brand Features

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. GFPE circuit breakers provide protection of equipment from damaging line-to-ground fault currents. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status at-a-glance.

*For applications up to 60A when using copper wire; or 50A when using aluminum wire

Item Description

Branch Circuit Breaker, GFPE 1-Pole 20A 120V, 10Ka Interrupt Rating

Technical Information

Product Features Standards & Certifications Operating Temperature: -40°C to 85°C CSA-C22.2 No. 5-02: Yes **EMC Compatibility:** Yes **Electrical Specifications**

FCC: Yes Amperage: 20 A RoHS: Yes Pole: 1 UL 489: Yes Short Circuit Current Rating: 10 KA **UL 943**: Yes

Type: GFPE

Voltage: 120 VAC

SPECIFICATION SUBMITTAL

	or got for from the	
ı	JOB NAME:	CATALOG NUMBERS:
ı		
	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

